

Integrated Controler

KDH-KZ3000-IP-U





The KDH-KZ3000-IP-U_M controller has been designed for access control system and to be mounted on a wall without any additional enclosure. 32 bit processor ensures fast and reliable data processing. This is one door controller. With additional reader (also with keypad) it can use for two way control.It's possibility to set one from four identification mode: Card only (default mode); PIN only; Card or PIN; Card + PIN

KDH-KZ3000-IP-U_M can work in standalone (programming from keypad) or in network mode. In network mode it can work on-line or off-line with supervisor **NOVUS MANAGMENT SYSTEM AC** software on PC.

| Readers port quantity | 1 |
|---------------------------|--|
| Double-sided acces point | 1 |
| One-side acces point | 1 |
| Standalone mode | yes |
| Card buffer | 20 000 (2000 in aoutonomous mode) |
| Event buffer | 50 000 |
| Inputs | 3 |
| Outputs | 3 |
| Supply power | 12 VDC / 1 A |
| Lock output type | relay |
| Doors | 1 |
| Readers port type | Wiegand 26 bit |
| Communication port | TCP/IP |
| User identification mode | card, pin, card + pin, cart or pin |
| Card reading standard | UNIQUE |
| Frequency | 125 kHz |
| Read range | 2 - 5 cm |
| PIN length | 6 |
| Inputs | exit button, sensor door opening, PIR sensor |
| Outputs | lock, bell, alarm |
| Anti-Passback | only with PC |
| Interlock | yes |
| Tamper | yes |
| Latch mode | yes |
| Standby current | 500mA |
| Humidity (non-condensing) | 0% - 95% |
| Temperature range | 2 to 55 °C |
| Dimensions (mm) | 122 x 77 x 39 |

