

Integrated Controler

KDH-KZ3000-IP-M





The KDH-KZ3000-IP-U_M controller has been designed for access control system and to be mounted on a wall without any additional enclosure. 32 bit processor ensures fast and reliable data processing. This is one door controller. With additional reader (also with keypad) it can use for two way control.It's possibility to set one from four identification mode: Card only (default mode); PIN only; Card or PIN; Card + PIN

KDH-KZ3000-IP-U_M can work in standalone (programming from keypad) or in network mode. In network mode it can work on-line or off-line with supervisor **NOVUS MANAGMENT SYSTEM AC** software on PC.

Double-side acces point1One-side acces point1Standalone modeyesCard buffer20 000 (2000 in aoutonomous mode)Event buffer50 000Inputs3Outputs3Supply power12 VDC / 1 ALock output typerelayDors1Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard ange frage2-5 cmIN length6Inputscard, bin, sensor door opening, PIR sensorOutputsoutputs PCAnti-Passbackonly with PCInterlockyesTamperyesStandby currentSoomAStandby currentSoomA	Readers port quantity	1
Standalone modeyesCard buffer20 000 (2000 in aoutonomous mode)Event buffer50 000Inputs3Outputs3Supply power12 VDC / 1 ALock output typerelayDoors1Readers port typeWiegand 34 bitCommication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE*Frequency13,56 MHzRead range2 - 5 cmINI length6Inputsexit button, sensor door opening, PIR sensorOutputsonly with PCInterlockyesTamperyesLatch modeyesStandby currentS00mA	Double-sided acces point	1
Card buffer20 000 (2000 in aoutonomous mode)Event buffer50 000Inputs3Outputs3Supply power12 VDC / 1 ALock output typerelayDoors1Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE*Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputsonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	One-side acces point	1
Event buffer50 000inputs3Outputs3Supply power12 VDC / 1 ALock output typerelayDoors1Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE®Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modesesStandby current500mA	Standalone mode	yes
inputs3Outputs3Supply power12 VDC / 1 ALock output typerelayDoors1Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE®Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputsonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Card buffer	20 000 (2000 in aoutonomous mode)
Outputs3Supply power12 VDC / 1 ALock output typerelayDoors1Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE®Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputsIock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch mode\$00mA	Event buffer	50 000
Supply power12 VDC / 1 ALock output typerelayDoors1Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE®Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbacknoll with PCInterlockyesTamperyesLatch modesensorStandby current500mA	Inputs	3
Lock output typerelayLock output typerelayDoors1Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE®Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modesomAStandby current500mA	Outputs	3
Doors1Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE®Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Supply power	12 VDC / 1 A
Readers port typeWiegand 34 bitCommunication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE*Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Lock output type	relay
Communication portTCP/IPUser identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE®Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Doors	1
User identification modecard, pin, card + pin, cart or pinCard reading standardMIFARE*Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Readers port type	Wiegand 34 bit
Card reading standardMIFARE*Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Communication port	TCP/IP
Frequency13,56 MHzRead range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	User identification mode	card, pin, card + pin, cart or pin
Read range2 - 5 cmPIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Card reading standard	MIFARE®
PIN length6Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Frequency	13,56 MHz
Inputsexit button, sensor door opening, PIR sensorOutputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Read range	2 - 5 cm
Outputslock, bell, alarmAnti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	PIN length	6
Anti-Passbackonly with PCInterlockyesTamperyesLatch modeyesStandby current500mA	Inputs	exit button, sensor door opening, PIR sensor
InterlockyesTamperyesLatch modeyesStandby current500mA	Outputs	lock, bell, alarm
Tamper yes Latch mode yes Standby current 500mA	Anti-Passback	only with PC
Latch modeyesStandby current500mA	Interlock	yes
Standby current 500mA	Tamper	yes
	Latch mode	yes
Humidity (non-condensing) 0% - 95%	Standby current	500mA
Hamary (non-condensing) 070 - 5570	Humidity (non-condensing)	0% - 95%
Temperature range 2 to 55 °C	Temperature range	2 to 55 °C
Dimensions (mm) 122 x 77 x 39	Dimensions (mm)	122 x 77 x 39

