# 8-port PoE+ Switch

## NVS-3308SP

## KEY FEATURES

NDAA

## KEY FEATURES

- 8 x 100Mbps PoE+
- 2 x Combo (RJ45 + SFP) 1000Mb/s UPLINK
- Operation mode: VLAN, Extend

## DIMENSIONS

## GENERAL

| | |
|---|---|
| Device Type | PoE+ Switch |

## NETWORK

| | |
|---|---|
| Ports | PoE+ Ports: 8 x 10/100Mbps (the number of ports simultaneously operating with PoE + mode is limited by PoE budget) • Uplink Combo x 2 :SFP(1Gb/s) + RJ45(1Gb/s) |
| PoE standards | IEEE802.3af, Class 3, IEEE802.3at, Class 4 |
| PoE modes | Endspan (1,2+ / 3,6-) |
| Switching capacity | 5.6 Gb/s |
| Protocols Support | IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3z 1000BASE-SX\LX |
| MAC address list | 4K |

## FUNCTIONS

| | |
|---|---|
| CCTV | Extended mode switch that increases the data and power transmission distance up to 200m (Using 10 Mb/s bandwidth) |
| Additional operating modes | VLAN, Extend |

## INSTALLATION PARAMETERS

| | |
|---|---|
| RACK Mount 19" | 1U |
| Case | Metal, color navy blue |
| Dimensions (mm) | 270 (W) x 44 (H) x 180 (L) |
| Weight | 1.2 kg |
| Input Voltage | 100 ~ 240 VAC, 50/60Hz |
| Power Consumption | 130 W (maximum) |
| PoE Budget | 120 W for ports 1 to 8, up to 30 W for one port |
| Operating Temperature | 0°C ~ 40°C |