NOVUS

Multistandard AHD Recorder

NHDR-4304-H1





KEY FEATURES



























- •Video channels: 4, audio channels: 4
- •Recording speed: up to 120 fps (AHD), up to 180 fps
- \bullet Internal HDDs mount: up to 1
- •Monitor outputs: 3 (2 x main, 1 x spot)
- •Supports HD analog cameras (720p, 1080p, 4MPX, 5MPX, 8MPX)
- •Supports AHD, TVI, CVI cameras
- •IP cameras support (hybrid mode)
- •Intelligent image analysis
- •PIR cameras support

COMPLIANCE



DIMENSIONS

VIDEO

Video Input	4 x BNC
Operating mode	AHD 8Mpx, TVI 8Mpx, CVI 8Mpx, analog 960H
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 x VGA (FullHD) • spot: 1 x BNC
IP Streams	DVR mode: $4 \times BNC + 0 \times IP \cdot hybrid mode: 4 \times BNC + 2 \times IP \cdot IP mode: 0 \times BNC + 6 \times IP$
Supported IP resolution	max. 3840 x 2160
AUDIO	

AUDIO

Audio Input/Output	4 x RCA (Line-in)/1 x HDMI, 1 x RCA

RECORDING

Compression	H.264, H.265
Recording Speed	120 fps (1280 x 720 - HD) • 120 fps (1920 x 1080 - FullHD) • 60 fps (2560 x 1440 - 4Mpx) • 48 fps (2560 x 1944 - 5Mpx) • 28 fps (3840 x 2160 - 8Mpx)
IP recording speed	hybrid mode: 60fps • IP mode: 180fps

· · · · · · · · · · · · · · · · · · ·
hybrid mode: 12 Mb/s in total from all IP cameras • IP mode: 36 Mb/s in total from all IP cameras
continuous, triggered by: REC/PANIC button, alarm input, motion detection, PIR alarm, image analysis

individual settings for: each camera, each day of the week,

configuration with an accuracy of: 30 min, possibility of combining individual recording modes Prealarm/postalarm up to 3 s/up to 5 min

PLAYBACK

Schedule

Playback speed	120 fps
IP playback speed	120 fps
Recorded Data Search	by date/time, events, image analysis events, motion in a defined area, tags

BACKUP

Backup Methods	USB port (HDD or Flash memory), network	
Backup File Format	JPG, BMP, PNG, MP4, AVI	
STORAGE		
Internal storage	available mount: 1 x HDD 3.5" SATA	
Tatal lata and Consolts	10 TD	

STORAGE		
Internal storage	available mount: 1 x HDD 3.5" SATA	
Total Internal Capacity	10 TB	
External storage	Network HDD (NFS or SMB/CIFS)	
Total External Capacity	64 TB	



NoVus

300 mm

Multistandard AHD Recorder NHDR-4304-H1

Λ	IΛ		М
A	ᅜ	n	ĮΥĮ

Alarm Input/Output	4/1 relay type
IP Camera Alarm Input/Output	supports IP camera's alarm input/output
Motion Detection	30 x 44 grid, individual settings of sensitivity, PIR cameras support
System Reaction to Alarm Events	buzzer, e-mail, alarm output activation, screen message, recording activation, PTZ, Full Screen, FTP picture upload, FTP video upload, picture to Cloud, video to Cloud

INTELLIGENT IMAGE ANALYSIS

Number of channels	4 x BNC, 6 x IP (4000 Serie)
Supported functions for analog cameras	Exception, Line cross, Zone entrance, Pedestrian detestion, Sound detection
Supported functions for IP cameras	Exception, Line cross, Zone entrance, Abandoned object, Object disappearance, Face detection, Pedestrian detestion, Cross counting, Sound detection

NETWORK	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, SNTP, RTSP, UPnP, SNMP, SMTP, P2P, HTML5
PC/MAC Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, NHDR-5000 Viewer, Firefox, Chrome, Opera, Edge, N Control 4000/Safari, NHDR-5000 Viewer, N Control 4000
Mobile applications	RxCamView (iPhone, Android)
Number of Simultaneous Conne	ctionsup to 32 users, each user up to 5 devices
Bandwidth	48 Mb/s in total to all client workstations

PTZ

PTZ Ports	1 x RS-485
PTZ Protocols	Pelco-D, Pelco-P
PTZ Functions	pan/tilt/zoom, preset commands, patterns

COAX

COAX Functions menu, zoom, focus, PTZ

AUXILIARY INTERFACES

USB Ports 2 x USB 2.0

OPERATING SYSTEM

Operating System	Linux
OSD	languages: Polish, English, Russian, others
Control	PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard
System Diagnostic	automatic control of: HDDs, camera connection loss
Security	password protection, IP filtering

INSTALLATION PARAMETERS

Dimensions (mm)	300 (W) x 53 (H) x 227 (D)	
Weight	1.1 kg (without HDD)	
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)	







Multistandard AHD Recorder NHDR-4304-H1

Power Consumption	20 W (with 1 HDD)
Operating Temperature	-10°C ~ 55°C

The recorder is dedicated to work with AHD cameras, Novus 4000 series IP cameras and achieves the best functionality with them. In case of work with IP cameras intelligent image analysis, dualstream mode, PTZ control, motion detection and alarm inputs / outputs functions depend on the functionality of the IP camera and the capabilities of the communication protocol. Detailed data on camera compatibility with recorders and compatible hard drives can be found in the compatibility tables available in the DOWNLOADABLE FILES

Display and playback speeds are achieved using dual stream. The recording speed of analog cameras may be limited during playback.



