NOVUS

Speed Dome IP Camera with face recognition and intelligent object tracking

NVIP-2SD-6540/25/F





KEY FEATURES





















- •Resolution: 2 MPX
- •Lens: motorized varifocal, Al and AF function, optical zoom 25x, f=4.8 \sim 120 mm/F1.65 \sim 3.8
- •D/N function IR cut filter
- •Auto Tracking
- •Video content analysis based on Deep Learning
- •microSD card support
- •WDR with double scan sensor
- •Min. Illumination from 0.001 lx (0 lx, IR on)
- •IR LED, range up to 150 m (depends on current optical zoom value)

DIMENSIONS

The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the $\ensuremath{\mathsf{DOWNLOADABLE}}$ FILES tab.

IMAGE

IMAGE	
Image Sensor	2 MPX CMOS sensor 1/2.8" SONY
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.005 lx/F1.65 - color mode • 0.001 lx/F1.65 - B/W mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto: 1 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

LENS

Optical Zoom	25x
Lens Type	motorized, auto-iris function, f=4.8 \sim 120 mm/F1.65 \sim F3.8
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Schedule	yes
Visible Light Sensor	ves

NETWORK

1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 704 x 480, 640 x 480 (VGA), 352 x 288 (CIF), 352 x 240
30 fps for each resolution
number of streams: 3
H.264, H.265, MJPEG/-
nsmax. 6
50 Mb/s in total






NoVus




300 mm



82 mm 116 mm

115 mm



Speed Dome IP Camera with face recognition and intelligent object tracking

NVIP-2SD-6540/25/F

Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE $802.1X$, PPPoE, SMTP, RTCP, ICMP
ONVIF Protocol Support	Profile S
Camera Configuration	from Internet Explorer browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	SuperLive Plus (iPhone, Android)
PTZ	
Preset Commands	360 including 20 special (function) presets
Tours	8 (up to 16 presets per tour)
Patterns	4 (max. 360 commands or 180 s for each pattern)
Tilt/Pan Range	-3° ~ 90°/360° (continuous)
Pan/Tilt Speed	up to 80°/s (proportional to zoom)
Preset Speed	up to 80°/s
VIDEO ANALYTICS	

Functions	auto tracking linked to Video Content Analysis (VCA) functions,
	tamper, line cross, zone entrance, zone exit, cross counting, scene
	change, video blurred, video color cast, zone entrance detection and
	object tracking, objects distinguishing, face recognition

OTHER FUNCTIONS

Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, object tracking
Restoring default settings	via web browser, via NMS IPTool software

IR LED

LED Number	6
Range	up to 150 m (depends on current optical zoom value)
Smart IR	yes (hardware support)

INTERFACES

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB

INSTALLATION PARAMETERS

Dimensions (mm)	173 (Φ) x 268 (H) with bracket: 173 (W) x 415 (H) x 300 (L)
Weight	2.1 kg with bracket: 2.8 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, IK10 impact rating, In set: outdoor housing (integrated with the camera), wall mount bracket
Power Supply	12 VDC, PoE+ (IEEE 802.3at, Klasa 4)
Surge protection	TVS 4000 V
Power Consumption	6 W • 15.5 W (IR illuminator on) • 22 W (IR and heater on)





Speed Dome IP Camera with face recognition and intelligent object tracking NVIP-2SD-6540/25/F

Operating Temperature	-30°C ~ 55°C
Cold start temperature	-20°C
Humidity	max. 90%, relative (non-condensing)
Built-in Heater/Fan	yes/yes

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).

