NOVUS

Multistandard AHD Recorder

NHDR-4308-H2





KEY FEATURES



























- •Recording speed: up to 240 fps (AHD), up to 360 fps
- •Internal HDDs mount: up to 2
- •Monitor outputs: 3 (2 x main, 1 x spot)
- •Supports HD analog cameras (720p, 1080p, 4MPX, 5MPX, 8MPX)
- •Supports AHD, TVI, CVI cameras
- •IP cameras support (hybrid mode)
- •Intelligent image analysis
- •PIR cameras support

COMPLIANCE



DIMENSIONS

VIDEO

Video Input	8 x BNC
Operating mode	AHD 8Mpx, TVI 8Mpx, CVI 8Mpx, analog 960H
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 x VGA (FullHD) • spot: 1 x BNC
IP Streams	DVR mode: 8 x BNC + 0 x IP • hybrid mode: 8 x BNC + 4 x IP • IP mode: 0 x BNC + 12 x IP
Supported IP resolution	max. 3840 x 2160
AUDIO	

AUDIO

Audio Input/Output	8 x RCA (Line-in)/1 x HDMI, 1 x RCA
--------------------	-------------------------------------

RECORDING

Compression	H.264, H.265
Recording Speed	240 fps (1280 x 720 - HD) • 240 fps (1920 x 1080 - FullHD) • 120 fps (2560 x 1440 - 4Mpx) • 96 fps (2560 x 1944 - 5Mpx) • 56 fps (3840 x 2160 - 8Mpx)
IP recording speed	hybrid mode: 120fps • IP mode: 360fps

IP stream size	hybrid mode: 24 Mb/s in total from all IP cameras • IP mode: 72 Mb/s in total from all IP cameras
Recording Mode	continuous, triggered by: REC/PANIC button, alarm input, motion detection, PIR alarm, image analysis

Schedule individual settings for: each camera, each day of the week, configuration with an accuracy of: 30 min, possibility of combining individual recording modes

Prealarm/postalarm up to 3 s/up to 5 min

PLAYBACK

Playback speed	240 fps
IP playback speed	240 fps
Recorded Data Search	by date/time, events, image analysis events, motion in a defined area, tags

BACKUP

Backup Methods	USB port (HDD or Flash memory), network	
Backup File Format	JPG, BMP, PNG, MP4, AVI	
STORAGE		
Internal storage	available mount: 2 x HDD 3 5" SATA	

nternal storage	available mount: 2 x HDD 3.5" SATA

Total Internal Capacity	16 TB
External storage	Network HDD (NFS or SMB/CIFS)
Total External Capacity	64 TB



NoVus



Multistandard AHD Recorder NHDR-4308-H2

Alarm Input/Output	8/1 relay type
IP Camera Alarm Input/Output	supports IP camera's alarm input/output
Motion Detection	30 x 44 grid, individual settings of sensitivity, PIR cameras support
System Reaction to Alarm Events	buzzer, e-mail, alarm output activation, screen message, recording activation, PTZ, Full Screen, FTP picture upload, FTP video upload, picture to Cloud, video to Cloud

INTELLIGENT IMAGE ANALYSIS

Number of channels	8 x BNC, 12 x IP (4000 Serie)
Supported functions for analog cameras	Exception, Line cross, Zone entrance, Sound detection
Supported functions for IP cameras	Exception, Line cross, Zone entrance, Abandoned object, Object disappearance, Face detection, Pedestrian detestion, Cross counting, Sound detection

NETWORK

NETWORK		
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s	
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, SNTP, RTSP, UPnP, SNMP, SMTP, P2P, HTML5	
PC/MAC Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, NHDR-5000 Viewer, Firefox, Chrome, Opera, Edge, N Control 4000/Safari, NHDR-5000 Viewer, N Control 4000	
Mobile applications	RxCamView (iPhone, Android)	
Number of Simultaneous Conne	ctionsup to 32 users, each user up to 5 devices	
Bandwidth	72 Mb/s in total to all client workstations	

PTZ

PTZ Ports	1 x RS-485
PTZ Protocols	Pelco-D, Pelco-P
PTZ Functions	pan/tilt/zoom, preset commands, patterns

COAX

COAX Functions menu, zoom, focus, PTZ

AUXILIARY INTERFACES

USB Ports 1 x USB 3.0, 1 x USB 2.0

OPERATING SYSTEM

Operating System	Linux
OSD	languages: Polish, English, Russian, others
Control	PC mouse and IR remote controller (in-set included), network, NV-KBD50 keyboard
System Diagnostic	automatic control of: HDDs, camera connection loss
Security	password protection, IP filtering

INSTALLATION PARAMETERS

Dimensions (mm)	378 (W) x 50 (H) x 340 (D)
Weight	2.5 kg (without HDDs)
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)







Multistandard AHD Recorder NHDR-4308-H2

Power Consumption	30 W (with 2 HDDs)
Operating Temperature	-10°C ~ 55°C

The recorder is dedicated to work with AHD cameras, Novus 4000 series IP cameras and achieves the best functionality with them. In case of work with IP cameras intelligent image analysis, dualstream mode, PTZ control, motion detection and alarm inputs / outputs functions depend on the functionality of the IP camera and the capabilities of the communication protocol. Detailed data on camera compatibility with recorders and compatible hard drives can be found in the compatibility tables available in the DOWNLOADABLE FILES

Display and playback speeds are achieved using dual stream. The recording speed of analog cameras may be limited during playback.



