

5 MPX IP Camera with video content analysis based on Deep Learning

NVIP-5VE-6501/F



KEY FEATURES



•Resolution: 5 MPX •Lens: fixed focal, f=2.8 mm/F1.6 •built-in microphone •D/N function - IR cut filter •Video content analysis based on Deep Learning •microSD card support •WDR with double scan sensor •Min. Illumination: 0.009 lx (0 lx, IR on) •IR LED, range up to 30 m

DIMENSIONS





The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

IMAGE

IMAGE	
Image Sensor	5 MPX CMOS sensor 1/2.7" OmniVision
Number of Effective Pixels	2688 (H) x 1944 (V)
Min. Illumination	0.009 lx/F1.6 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/3 s ~ 1/10000 s
Digital Slow Shutter (DSS)	up to 1/3 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
LENS	
Lens Type	fixed focal, f=2.8 mm/F1.6
DORI	
DORI (Detection, Observation, Recognition, Identification)	for f = 2.8mm - D: 61.2m, O: 24.3m, R: 12.2m, I: 6.1m
DAY/NIGHT	
Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 120 s
Switching Schedule	yes
Visible Light Sensor	yes
NETWORK	
Stream Resolution	2560 x 1440 (QHD), 2592 x 1520, 2592 x 1944, 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 704 x 480, 352 x 288 (CIF), 352 x 240, 480 x 240
Frame Rate	30 fps for • 60 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.264 Smart, H.265, H.265+, H.265 Smart, MIPEG/G.711



VART



5 MPX IP Camera with video content analysis based on Deep Learning NVIP-5VE-6501/F

Number of Simultaneous Connectionsmax. 10

Number of Simultaneous Connection	ISIIIdX. 10
Bandwidth	60 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, ICMP, SSL/TLS
Camera Configuration	from Internet Explorer browser ${\scriptstyle \bullet}$ languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	SuperLive Plus (iPhone, Android)
VIDEO ANALYTICS	
Functions	tamper, line cross, zone entrance, zone exit, object counting, multi loiter, face detection, pedestrian detection, cross counting, heat map scene change, video blurred, video color cast, objects distinguishing, people counting, vehicle counting, target counting by area
OTHER FUNCTIONS	
Privacy Zones	4 video mask type: single color
Motion Detection	yes
Region of interest (ROI)	8
Image Processing	180° image rotation, sharpening, mirror effect, corridor mode, vertical flip, horizontal flip, lens distortion correction
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card
Restoring default settings	via web browser, using reset button, via NMS IPTool software
IR LED	
LED Number	1
Range	30 m
Smart IR	yes (software support)
INTERFACES	
Audio Input/Output	1 x Jack (3.5 mm)/- • built-in microphone
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	
	microSD - capacity up to 256GB
INSTALLATION PARAMETERS	microSD - capacity up to 256GB
INSTALLATION PARAMETERS Dimensions (mm)	microSD - capacity up to 256GB 97 (Φ) x 83 (H)
Dimensions (mm)	97 (Φ) x 83 (H)
Dimensions (mm) Weight	97 (Φ) x 83 (H) 0.5 kg
Dimensions (mm) Weight Degree of Protection	97 (Φ) x 83 (H) 0.5 kg IP 67 (details in the user's manual) vandalproof, IK10 impact rating, aluminium, white • enclosure type:
Dimensions (mm) Weight Degree of Protection Enclosure	97 (Φ) x 83 (H) 0.5 kg IP 67 (details in the user's manual) vandalproof, IK10 impact rating, aluminium, white • enclosure type: 6VE-S
Dimensions (mm) Weight Degree of Protection Enclosure Power Supply	97 (Φ) x 83 (H) 0.5 kg IP 67 (details in the user's manual) vandalproof, IK10 impact rating, aluminium, white • enclosure type: 6VE-S 12 VDC, PoE (IEEE 802.3af, Klasa 3)
Dimensions (mm) Weight Degree of Protection Enclosure Power Supply Surge protection	97 (Φ) x 83 (H) 0.5 kg IP 67 (details in the user's manual) vandalproof, IK10 impact rating, aluminium, white • enclosure type: 6VE-S 12 VDC, PoE (IEEE 802.3af, Klasa 3) TVS 4000 V





5 MPX IP Camera with video content analysis based on Deep Learning NVIP-5VE-6501/F

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).

