

Bullet IP Camera with Motor-zoom Lens

NVIP-5H-4502M/F



KEY FEATURES



- Resolution: 5 MPX
- Lens: motorized, auto-focus function, $f=2.7 \sim 13.5$ mm/F1.8
- support for Chrome, Firefox, Opera, Safari browsers
- D/N function - IR cut filter
- Video content analysis based on Deep Learning
- Licence plate recognition (LPR)
- microSD card support
- WDR with double scan sensor
- two-way audio
- Min. Illumination: 0.03 lx (0 lx, IR on)
- IR LED, range up to 45 m
- "Two way power" - when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

COMPLIANCE



DIMENSIONS

The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the **DOWNLOADABLE FILES** tab.

IMAGE

Image Sensor	5 MPX CMOS sensor 1/2.7" OmniVision
Number of Effective Pixels	2592 (H) x 1944 (V)
Min. Illumination	0.03 lx/F1.2 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Reduction of image flicker (Antiflicker)	yes

LENS

Lens Type	motorized, $f=2.7 \sim 13.5$ mm/F1.8
Auto-focus	zoom trigger, manual trigger

DORI

DORI (Detection, Observation, Recognition, Identification)	for $f = 2.7$ mm - D: 56m, O: 22.4m, R: 11m, I: 5.6m • for $f = 13.7$ mm - D: 240m, O: 96m, R: 48m, I: 24m
--	--

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Delay	1 ~ 36 s
Visible Light Sensor	yes

NETWORK

Stream Resolution	2592 x 1520, 2592 x 1944, 2304 x 1296, 1920 x 1080 (Full HD), 2048 x 1536 (QXGA), 1280 x 960, 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.265, H.265+/G.711
Number of Simultaneous Connections	max. 10
Bandwidth	60 Mb/s in total

Bullet IP Camera with Motor-zoom Lens NVIP-5H-4502M/F



Network Protocols Support	HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, SMTP, P2P, HTML5
Camera Configuration	from Internet Explorer, Firefox, Chrome, Opera, Safari browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC
Mobile applications	ipGO 4 (iPhone, Android)

VIDEO ANALYTICS

Functions	abandoned object, object disappearance, line cross, zone entrance, zone exit, zone violation, multi loiter, pedestrian detection, cross counting, heat map, queue length detection, objects distinguishing, face recognition, vehicle detection, comparing faces, intrusion detection, smart motion detection with objects distinguishing
-----------	---

OTHER FUNCTIONS

Privacy Zones	4 video mask type: single color
Motion Detection	yes
Audio Detection	
Image Processing	180° image rotation, vertical flip, horizontal flip
Prealarm/Postalarm	up to 5 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation, saving in the cloud storage
Restoring default settings	via web browser, using reset button

LICENCE PLATE RECOGNITION (LPR)

Autonomous operation mode	yes - recognition function implemented in the camera
Capacity of License Plate Database	up to 10000 license plates, on all lists.
Types of recognized number plates	all countries of the European Union
Barrier control	yes - built-in relay output
Data recorded in the camera base	recognition date/time, number of recognised licence plate, image of recognised licence plate, presence on the "white list" or "black list"
Reactions for the licence plate recognition	e-mail with attachment, saving file on FTP server, alarm output activation

IR LED

LED Number	4
Range	45 m
Smart IR	yes (hardware support)

INTERFACES

Audio Input/Output	1 x RCA/1 x RCA
Alarm Input/Output	1 (NO/NC)/1 relay type (max. 12VDC/300mA)
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 87 (W) x 83 (H) x 242 (L)
Weight	0.82 kg
Degree of Protection	IP 66 (details in the user's manual)
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)

Bullet IP Camera with Motor-zoom Lens **NVIP-5H-4502M/F**

Surge protection	TVS 4000 V
Power Consumption	2 W • 5 W (IR illuminator on)
Operating Temperature	-30°C ~ 55°C
Humidity	max. 95%, relative (non-condensing)

A memory card is required for the face recognition and license plate recognition functions to work. The license plate recognition function is available for cameras with firmware V21.45.8.2.3_xxxx