

NMS Client Station

NMS CLIENT 7-T-III



KEY FEATURES



KEY FEATURES

- Monitoring of up to 70 channels
- Supports resolution up to 4000 x 3000
- Supports up to 6 monitors simultaneously
- Operating system: Microsoft Windows 10 IoT
- Recording and surveillance system: NMS (Novus Management System)
- Compatible with all NMS Network Video Recorders
- Integration with: recorders AHD NOVUS, systems of SSWiN DSC, systems of NMS ANPR, systems POS (Posnet, Upos i inne)

DIMENSIONS



VIDEO

IP Cameras up to 70 channels at 640 x 480 resolution resolution using H.264 codec (video + audio) • up to 55 channels at 640 x 480 resolution resolution using H.265 codec (video + audio)

Maximum Supported Camera Resolution 4000 x 3000

Supported Codes H.264, H.264+, H.265, H.265+, MJPEG

Supported Protocols Novus, ONVIF, RTSP

Dualstreaming Support yes

DISPLAY

Monitor Output 2 x HDMI 2.0b, 2 x Display Port 1.4, 2 x Dual link DVI-D, (up to 6 monitors simultaneously)

Maximum Resolution 6 x 4K UltraHD

AUDIO

Audio input 1 x Line in (3,5mm), 1 x Mic in(3,5mm)

Audio Output 1 x Line output (3,5mm), 2 x HDMI, 2 x Display Port

PERFORMANCE - H.264

2MPX IP Camera Display up to: 70 sub streams or 20 main streams • Playback up to: 20 main streams

4MPX IP Camera Display up to: 70 sub streams or 13 main streams • Playback up to: 13 main streams

5MPX IP Camera Display up to: 60 sub streams or 8 main streams • Playback up to: 8 main streams

8MPX IP Camera Display up to: 40 sub streams or 5 main streams • Playback up to: 5 main streams

12MPX IP Camera Display up to: 35 sub streams or 8 main streams • Playback up to: 8 main streams

PERFORMANCE - H.265

2MPX IP Camera Display up to: 55 sub streams or 15 main streams • Playback up to: 15 main streams

4MPX IP Camera Display up to: 50 sub streams or 8 main streams • Playback up to: 8 main streams

5MPX IP Camera Display up to: 60 sub streams or 5 main streams • Playback up to: 5 main streams

8MPX IP Camera Display up to: 65 sub streams or 4 main streams • Playback up to: 4 main streams

12MPX IP Camera Display up to: 32 sub streams or 4 main streams • Playback up to: 4 main streams

PLAYBACK

Recorded Data Search by date/time, events, "Text-in"

BACKUP

Backup Methods USB port (HDD or Flash memory), network

STORAGE

Internal storage for system built-in: 1 x SSD NVMe

NETWORK

Network Interface 1 x Ethernet - RJ-45 interface, 10/100/1000/2500 Mbit/s

Bandwidth 350 Mb/s in total from all NVRs

Network Protocols Support HTTP, TCP/IP, IPv4/v6, UDP, FTP, DHCP, DNS, NTP, RTSP, UPnP, SMTP

Mobile applications NMS Mobile

PTZ

PTZ Functions pan/tilt/zoom, preset commands, patterns, tours, auto-scans

AUXILIARY INTERFACES

USB Ports 4 x USB 2.0, 4 x USB 3.2, 1 x USB 3.2 Type-C

OPERATING SYSTEM

Operating System Microsoft Windows 10 IoT

Recording and Surveillance System NMS (Novus Management System)

Operation Mode triplex

OSD languages: Polish, English, Russian, others

Control PC mouse and keyboard (in-set included), DCZ keyboard

System Diagnostic automatic control of: HDDs, network, camera connection loss

Security password protection, IP filtering, limiting the number of connections

INSTALLATION PARAMETERS

Dimensions (mm) 177 (W) x 483 (H) x 505 (D)

Weight 10 kg

Power Supply/Power Consumption built-in PSU 230 VAC/700 W

Power consumption/heatprint 350W/280W (without HDD for recording)

Operating Temperature 5°C ~ 35°C