## **NoVus**

## Bullet IP Camera Starlight PRO DUO

### **NVIP-2H-4231/WL**





#### **KEY FEATURES**





















- •Resolution: 2 MPX
- •Lens: fixed focal, f=3.6 mm/F1.0
- •built-in microphone
- •D/N function IR cut filter
- microSD card support
- •Min. Illumination: 0.0005 lx (0 lx, IR on)
- •IR LED, range up to 30 m
- •white LED illuminator, range up to 25 m
- "Two way power" when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

#### **COMPLIANCE**



#### **DIMENSIONS**

The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

#### **IMAGE**

Image Sensor	2 MPX CMOS sensor 1/2.7" SmartSens
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.0005 lx/F1.0 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

#### LENS

Lens Type	fixed focal, $f=3.6 \text{ mm/F}1.0$

#### DORI

DORI (Detection, Observation,	for f = 3.6mm - D: 48m, O: 19m, R: 9.6m, I: 5m
Recognition, Identification)	

#### **DAY/NIGHT**

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Delay	1 ~ 36 s
Switching Schedule	yes
Visible Light Sensor	yes

#### NETWORK

Stream Resolution	1920 x 1080 (Full HD), 640 x 480 (VGA)
Multistreaming Mode	number of streams: 2
Video/Audio Compression	H.264, H.265/G.711
Number of Simultaneous Conne	ctionsmax. 10
Bandwidth	40 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, SMTP, P2P





## **NoVus**









151 mm

# Bullet IP Camera Starlight PRO DUO NVIP-2H-4231/WL

Camera Configuration	from Internet Explorer browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS
Mobile applications	ipGO 4 (iPhone, Android)

#### **OTHER FUNCTIONS**

Privacy Zones	4 video mask type: single color
Motion Detection	yes
Image Processing	180° image rotation, vertical flip, horizontal flip
Prealarm/Postalarm	up to 5 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, saving in the cloud storage
Determent	white LEDs, steady/flashing light,
Restoring default settings	via web browser, using reset button

#### IR LED

LED Number	2
Range	30 m
Smart IR	ves (hardware support)

#### WHITE LIGHT ILLUMINATOR

LED Number	2, warm white color
Range	25 m
Smart Light	ves (hardware support)

#### **INTERFACES**

Audio Input/Output	built-in microphone
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB

#### **INSTALLATION PARAMETERS**

with bracket: 74 (Φ) x 151 (L)  0.38 kg  IP 66 (details in the user's manual)
· · · · · ·
IP 66 (details in the user's manual)
in oo (details in the daer 3 mandar)
12 VDC, PoE (IEEE 802.3af, Class 3)
TVS 4000 V
1.2 W • 3.5 W (IR illuminator on) • 3.3 W (white light illuminator on) • 5.6 W (IR and white light illuminators on)
-30°C ~ 60°C
max. 95%, relative (non-condensing)
1

