
NoVus

NMS IP Recorder

NMS NVR X-4U-III





KEY FEATURES















- •Video and audio channels: 200
- •Supports resolution up to 4000 x 3000
- •Recorded stream size: 450 Mb/s in total from all
- $\bullet \text{Supports up to 3 monitors simultaneously} \\$
- •optional disk mounting: 8 x SATA 3,5"
- •External arrays support
- •Operating system: Microsoft Windows 10 IoT
- •Compatible with all NOVUS IP cameras

DIMENSIONS





AIDEC

IP Camera Recording	160 channels at 1920x1080 (video+audio) using H.264 codec • 200
	channels at 1920x1080 (video+audio) using H.265 codec
Maximum Supported Camera Resolution	4000x3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Cameras and Protocols	Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye
Dualstreaming Support	yes
DISPLAY	
Monitor Output	1 x HDMI 2.0b, 1 x Dual link-DVI, 1 x Display Port 1.2 (up to 3 monitors simultaneously)
Maximum Resolution	3 x 4K UltraHD
AUDIO	
Audio Output	1 x HDMI, 1 x Display Port
PERFORMANCE - H.264	
2MPX IP Camera	Recording up to: 160 main streams (while displaying: 8 sub streams) • Display up to: 60 sub streams or 20 main streams (while recording 80 main streams) • Playback up to: 20 main streams (while recording: 80 main streams)
4MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 50 sub streams or 13 main streams (while recording 80 main streams) • Playback up to: 13 main streams (while recording: 80 main streams)
5MPX IP Camera	Recording up to: 100 main streams (while displaying: 8 sub streams) • Display up to: 40 sub streams or 8 main streams (while recording: 80 main streams) • Playback up to: 8 main streams (while recording: 80 main streams)
8MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) Display up to: 30 sub streams or 5 main streams (while recording: 60 main streams) • Playback up to: 5 main streams (while recording: 60 main streams)
12MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) Display up to: 25 sub streams or 4 main streams (while recording: 50 main streams) • Playback up to: 4 main streams (while recording: 50 main streams)

2MPX IP Camera	Recording up to: 200 main streams (while displaying: 8 sub streams) • Display up to: 60 sub streams or 20 main streams (while recording: 80 main streams) • Playback up to: 20 main streams (while recording: 80 main streams)
4MPX IP Camera	Recording up to: 160 main streams (while displaying: 8 sub streams) • Display up to: 40 sub streams or 9 main streams (while recording: 80 main streams) • Playback up to: 9 main streams (while recording: 80 main streams)

NoVus

NMS IP Recorder NMS NVR X-4U-III

5MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 35 sub streams or 4 main streams (while recording: 70 main streams) • Playback up to: 4 main streams (while recording: 70 main streams)
8MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) • Display up to: 25 sub streams or 4 main streams (while recording: 70 main streams) • Playback up to: 4 main streams (while recording: 70 main streams)
12MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) • Display up to: 16 sub streams or 4 main streams (while recording: 50 main streams) • Playback up to: 4 main streams (while recording: 50 main streams)
RECORDING	
Recording Mode	Continuous, Schedule, Panic, Triggered: manually, by alaram input, motion detection, video analysis, POS, temerature alarm
Schedule	individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes
Prealarm/Postalarm	Up to: 30s / Up to: 600s
PLAYBACK	
Recorded Data Search	By Date/Time, Events, "Text-in", Image Analysis Events
BACKUP	
Backup Methods	USB port (HDD lor Flash drive), Network
Backup File Format	JPEG, BMP, AVI, NMS
HDD	
Internal storage for system	1 x SSD NVMe
Internal storage for system Internal Storage for Recording	1 x SSD NVMe 8 available bays for 3,5" HDD surveillance grade storage media
Internal Storage for Recording	
Internal Storage for Recording	8 available bays for 3,5" HDD surveillance grade storage media
Internal Storage for Recording ALARMS Alarm Input/output in cameras	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR)	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface Network Throughput	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP,
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface Network Throughput Network Protocols Support	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, SAMBA
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface Network Throughput Network Protocols Support Compatible Mobile Applications	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, SAMBA
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface Network Throughput Network Protocols Support Compatible Mobile Applications PTZ	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, SAMBA NMS Mobile pan, tilt, zoom, preset commands, patterns, tours, auto-scans, focus,
Internal Storage for Recording ALARMS Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface Network Throughput Network Protocols Support Compatible Mobile Applications PTZ PTZ Functions	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, SAMBA NMS Mobile pan, tilt, zoom, preset commands, patterns, tours, auto-scans, focus,





NMS IP Recorder NMS NVR X-4U-III

Operating System	Microsoft Windows 10 IoT
Recording and Surveillance System	NMS (Novus Management System)
Additional Software	NMS, NOVUS MANAGEMENT SYSTEM AC, Internet Explorer
Operation Mode	Pentaplex
OSD	Polish, English, Russian, others
Control	PC mouse and keyboard (in-set included), DCZ keyboard
System Diagnostic	automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss
Security	Password protection, IP filtering, MAC filtering, Limiting the number of connections
INTEGRATION	
Integrated Devices	Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, NMS-ANPR Software, DSC Systems, POS Systems (Posnet, Upos and other), ONVIF Devices, RTSP Devices
INSTALLATION PARAMETERS	
Dimensions (mm)	178 (W) x 452 (H) x 648 (D)
Weight	28 kg (without HDD)
Power Supply	built in 700W, with 230VAC input • with Hot-Swap function (allowing to replace the power supply without turning off the unit)
Power consumption/heatprint	350W/280W (without HDD for recording)
Operating Temperature	5°C ~ 35°C
RACK Mount 19"	4U

^{*} To support more than two monitors it is required to use Display Port output.



^{***} Available with dual streaming mode.

*** Function capability depends on used devices and communication protocols.

**** List of compatible HDD models and maximum of their capacities is available in section DOWNLOADABLE FILES.