

NMS IP Recorder NMS NVR X-2U-III-144TB



PRO SERIES

KEY FEATURES

H	265			
×200	450 mb/s	A×12	3300 fps	Monitor
V+A	Stream	HDD	● REC	

VIDEO

•Video and audio channels: 200

•Supports resolution up to 4000 x 3000 •Recorded stream size: 450 Mb/s in total from all

cameras • Supports up to 3 monitors simultaneously

•Built-in HDDs: 12 x 12 TB server-dedicated SAS for 24/7 recording

•RAID controller protects recordings •External arrays support

•Operating system: Microsoft Windows 10 IoT •Recording and surveillance system: NMS (Novus

Management System) •Compatible with all NOVUS IP cameras

•Redundant PSUs: 2

DIMENSIONS



IP Camera Recording	160 channels at 1920x1080 (video+audio) using H.264 codec • 200 channels at 1920x1080 (video+audio) using H.265 codec	
Maximum Supported Camera Resolution	4000x3000	
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG	
Supported Cameras and Protocols	Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye	
Dualstreaming Support	yes	
DISPLAY		
Monitor Output	3 x Mini Display Port 1.2, (up to 3 monitors simultaneously)	
Maximum Resolution	3 x 4K UltraHD	
AUDIO		
Audio Output	3 x Mini Display Port 1.2	
PERFORMANCE - H.264		
2MPX IP Camera	Recording up to: 160 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 160 main streams) • Playback up to: 8 main streams (while recording: 160 main streams)	
4MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 120 main streams) • Playback up to: 8 main streams (while recording: 120 main streams)	
5MPX IP Camera	Recording up to: 100 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 100 main streams) • Playback up to: 8 main streams (while recording: 8 main streams)	
8MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 6 main streams (while recording: 80 main streams) • Playback up to: 6 main streams (while recording: 80 main streams)	
12MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 4 main streams (while recording: 80 main streams) • Playback up to: 4 main streams (while recording: 80 main streams)	
PERFORMANCE - H.265		
2MPX IP Camera	Recording up to: 200 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 200 main streams) • Playback up to: 8 main streams (while recording: 200 main streams)	
4MPX IP Camera	Recording up to: 160 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 160 main streams) • Playback up to: 8 main streams (while recording: 160 main streams)	





NMS IP Recorder NMS NVR X-2U-III-144TB

5MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 4 main streams (while recording: 120 main streams) • Playback up to: 4 main streams (while recording: 120 main streams)	
8MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) Display up to: 8 sub streams or 4 main streams (while recording: 90 main streams) • Playback up to: 4 main streams (while recording: 90 main streams)	
12MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) Display up to: 8 sub streams or 4 main streams (while recording: 90 main streams) • Playback up to: 4 main streams (while recording: 90 main streams)	
RECORDING		
Recording Mode	Continuous, Schedule, Panic, Triggered: manually, by alaram input, motion detection, video analysis, POS, temerature alarm	
Schedule	individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes	
Prealarm/Postalarm	Up to: 30s / Up to: 600s	
PLAYBACK		
Recorded Data Search	By Date/Time, Events, "Text-in", Image Analysis Events	
BACKUP		
Backup Methods	USB port (HDD lor Flash drive), Network	
Backup File Format	JPEG, BMP, AVI, NMS	
HDD		
Internal storage for system	1 x SSD NVMe	
Internal Storage for Recording	12 x 12TB SAS 3,5" surviliance grade server storage media	
RAID Redundancy	RAID types: RAID 0, RAID 1, RAID 5, RAID 6	
ALARMS		
Alarm Input/output in cameras	support of alarm input and output built in cameras	
Motion detection	support of motion detection built in cameras	
Video Analytics	supported built in analytics in camera	
Temperature alarm	support of temperature alarm built in cameras	
Licence plate recognition (LPR)	support of selected image analysis functions available in the camera	
NETWORK		
Network Interface	2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s	
Network Throughput	up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card	
Network Protocols Support		
	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, Multicast, FTP, DHCP, DNS, DDNS NTP, RTSP, SAMBA	
Compatible Mobile Applications	NTP, RTSP, SAMBA	
	NTP, RTSP, SAMBA	
Compatible Mobile Applications	NTP, RTSP, SAMBA NMS Mobile pan, tilt, zoom, preset commands, patterns, tours, auto-scans, focus	





NMS IP Recorder NMS NVR X-2U-III-144TB

OPERATING SYSTEM

•••••••••••••••••••••••••••••••••••••••		
Operating System	Microsoft Windows 10 IoT	
Recording and Surveillance System	NMS (Novus Management System)	
Additional Software	NMS, Internet Explorer	
Operation Mode	Pentaplex	
OSD	Polish, English, Russian, others	
Control	PC mouse and keyboard (in-set included), DCZ keyboard	
System Diagnostic	automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss	
Security	Password protection, IP filtering, MAC filtering, Limiting the number of connections	
INTEGRATION		
Integrated Devices	Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, NMS- ANPR Software, DSC Systems, POS Systems (Posnet, Upos and other) ONVIF Devices, RTSP Devices	
INSTALLATION PARAMETERS		
Dimensions (mm)	437 (W) x 89 (H) x 648 (D)	
Weight	24 kg (with HDDs)	
Power Supply	built in 2 x redundant power supply 230VAC input with 960W power each	
Power consumption/heatprint	490W/400W (without HDD for recording)	
Operating Temperature	5°C ~ 35°C	
RACK Mount 19"	20	

Attention: To support more than 1 RTSP stream and 1 ONVIF stream you will need special licence key.

