## **NoVus**

# Wall/ceiling mount bracket with built-in PoE switch

### NVS-4020JBD



#### **KEY FEATURES**

- •2 x 100Mbps PoE
- •1 x 100Mb/s UPLINK

#### **DIMENSIONS**



Wall/ceiling mount bracket, indoor/outdoor, for mounting two cameras.

A detailed list of compatible cameras and other products and accessories, can be found in the file available in the "Downloadable File" section.

#### **GENERAL**

Managed	no	
Device Type	PoE Switch	
NETWORK		
Ports	UPLINK ports: 1 x 10/100Mbps	

Ports	UPLINK ports: 1 x 10/100Mbps
PoE standards	IEEE802.3af, Class 3
Surge protection	Maximum voltage: 4kV
Switching capacity	1 Gb/s

#### **FUNCTIONS**

Surge protection yes

#### **INSTALLATION PARAMETERS**

Case	Glass fiber reinforced polyamide, color white
Dimensions (mm)	310 (W) x 70 (H) x 156 (L)
Weight	1.2 kg
Degree of Protection	IP 66 (details in the user's manual)
Input Voltage	PoE+
Power Consumption	30 W (maximum)
PoE Budget	25 W for ports 1 to 2, up to 15 W for one port
Operating Temperature	-30°C ~ 60°C
Humidity	max. 90%, relative (non-condensing)