

Wall/ceiling mount bracket with built-in PoE switch

NVS-4020JBD



KEY FEATURES

- 2 x 100Mb/s PoE
- 1 x 100Mb/s UPLINK

DIMENSIONS



Wall/ceiling mount bracket, indoor/outdoor, for mounting two cameras.

A detailed list of compatible cameras and other products and accessories, can be found in the file available in the "Downloadable File" section.

GENERAL

| | |
|-------------|------------|
| Managed | no |
| Device Type | PoE Switch |

NETWORK

| | |
|--------------------|--|
| Ports | PoE Ports: 2 x 10Mb/s / 100Mb/s • UPLINK ports: 1 x 10Mb/s / 100Mb/s |
| PoE standards | IEEE802.3af, Class 3 |
| Surge protection | Maximum voltage: 4kV |
| Switching capacity | 1 Gb/s |

FUNCTIONS

| | |
|------------------|-----|
| Surge protection | yes |
|------------------|-----|

INSTALLATION PARAMETERS

| | |
|-----------------------|--|
| Case | Glass fiber reinforced polyamide, color white |
| Dimensions (mm) | 310 (W) x 70 (H) x 156 (L) |
| Weight | 1.2 g |
| Degree of Protection | IP 66 (details in the user's manual) |
| Input Voltage | PoE+ |
| Power Consumption | 30 W (maximum) |
| PoE Budget | 25 W for ports 1 to 2, up to 15 W for one port |
| Operating Temperature | -30°C ~ 60°C |
| Humidity | max. 90%, relative (non-condensing) |