NoVus

Wall/ceiling mount bracket with built-in PoE switch

NVS-4020JBD



KEY FEATURES

- •2 x 100Mbps PoE
- •1 x 100Mb/s UPLINK

DIMENSIONS



Wall/ceiling mount bracket, indoor/outdoor, for mounting two cameras.

A detailed list of compatible cameras and other products and accessories, can be found in the file available in the "Downloadable File" section.

GENERAL

Managed	no	
Device Type	PoE Switch	
NETWORK		
Ports	UPLINK ports: 1 x 10/100Mbps	

Ports	UPLINK ports: 1 x 10/100Mbps
PoE standards	IEEE802.3af, Class 3
Surge protection	Maximum voltage: 4kV
Switching capacity	1 Gb/s

FUNCTIONS

Surge protection yes

INSTALLATION PARAMETERS

Case	Glass fiber reinforced polyamide, color white
Dimensions (mm)	310 (W) x 70 (H) x 156 (L)
Weight	1.2 kg
Degree of Protection	IP 66 (details in the user's manual)
Input Voltage	PoE+
Power Consumption	30 W (maximum)
PoE Budget	25 W for ports 1 to 2, up to 15 W for one port
Operating Temperature	-30°C ~ 60°C
Humidity	max. 90%, relative (non-condensing)