


8 MPX Speed Dome IP Camera with intelligent object tracking

NVIP-8SD-6540/25/F

6000 VSS
IP



KEY FEATURES



- Resolution: 8 MPX (4K Ultra HD)
- Lens: motorized varifocal, AI and AF function, optical zoom 25x, f=4.8 ~ 120 mm/F1.65 ~ 3.8
- D/N function - IR cut filter
- Auto Tracking
- Video content analysis based on Deep Learning
- microSD card support
- WDR with double scan sensor
- two-way audio
- Min. Illumination from 0.002 lx (0 lx, IR on)
- IR LED, range up to 150 m (depends on current optical zoom value)

COMPATIBILITY



DIMENSIONS

The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the **DOWNLOADABLE FILES** tab.

IMAGE

Image Sensor	8 MPX CMOS sensor 1/2.8" SONY STARVIS
Number of Effective Pixels	3864 (H) x 2192 (V)
Min. Illumination	0.01 lx/F1.65 - color mode • 0.002 lx/F1.65 - B/W mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/25 s ~ 1/30000 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

LENS

Optical Zoom	25x
Lens Type	motorized, auto-iris function, f=4.8 ~ 120 mm/F1.65 ~ F3.8
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DAY/NIGHT


Switching Type	mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	3840 x 2160 (4K Ultra HD), 2560 x 1440 (QHD), 1920 x 1080 (Full HD), 2048 x 1536 (QXGA), 1280 x 960, 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 352 x 288 (CIF)
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711
Number of Simultaneous Connections	max. 10
Bandwidth	80 Mb/s in total

8 MPX Speed Dome IP Camera with intelligent object tracking

NVIP-8SD-6540/25/F



Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, ICMP, HTML5, RTMP
ONVIF Protocol Support	Profile G/S/T
Camera Configuration	from Edge, Firefox, Chrome, Opera, Safari browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, N Control 6000
Mobile applications	N-VID6 (iPhone, Android)

PTZ

Preset Commands	360 including 20 special (function) presets
Tours	8 (up to 16 presets per tour)
Patterns	4 (max. 180 s for each pattern)
Tilt/Pan Range	-3° ~ 90°/360° (continuous)
Pan/Tilt Speed	up to 200°/s (proportional to zoom)
Preset Speed	up to 240°/s

VIDEO ANALYTICS

Functions	auto tracking linked to Video Content Analysis (VCA) functions, tamper, line cross, zone entrance, zone exit, cross counting, scene change, video blurred, video color cast, objects distinguishing, face recognition, intrusion detection
-----------	--

OTHER FUNCTIONS

Privacy Zones	8 video mask type: single color
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation, object tracking
Restoring default settings	via web browser, using reset button, via NMS IPTool software

IR LED

LED Number	6
Range	up to 150 m (depends on current optical zoom value)
Smart IR	yes (hardware support)

INTERFACES

Audio Input/Output	1 x Jack (3.5 mm)/1 x Jack (3.5 mm)
Alarm Input/Output	1 (NO/NC)/1 relay type
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB

INSTALLATION PARAMETERS

Dimensions (mm)	173 (Φ) x 268 (H) with bracket: 173 (W) x 415 (H) x 300 (L)
Weight	2.1 kg with bracket: 2.8 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, IK10 impact rating, in set: outdoor housing (integrated with the camera), wall mount bracket
Power Supply	12 VDC, PoE+ (IEEE 802.3at, Klasa 4)



8 MPX Speed Dome IP Camera with intelligent object tracking

NVIP-8SD-6540/25/F

Surge protection	TVS 4000 V
Power Consumption	6 W • 15.5 W (IR illuminator on) • 22 W (IR and heater on)
Operating Temperature	-40°C ~ 60°C
Cold start temperature	-30°C
Humidity	max. 90%, relative (non-condensing)
Built-in Heater/Fan	yes/yes

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).

