

Vandal Proof AHD Multistandard Camera NHDC-2VE-6101-II

6000 VSS MULTI HD



KEY FEATURES



- D/N function - IR cut filter
- resolution 1080p
- Lens: fixed focal, f=2.8 mm/F2.4
- Smart IR function
- multistandard: AHD, CVI, TVI, 960H
- IR LED, range up to 30 m

COMPLIANCE



DIMENSIONS



IMAGE

Image Sensor	CMOS sensor 1/3" SMARTSENS
Operating mode	AHD 1080p, AHD 720p, TVI 1080p, TVI 720p, CVI 1080p, CVI 720p, analog 960H
Number of Effective Pixels	1920 (H) x 1080 (V)
Resolution	1080p
Min. Illumination	0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/50 s ~ 1/100000 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D

LENS

Lens Type	fixed focal, f=2.8 mm/F2.4
-----------	----------------------------

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual

OTHER FUNCTIONS

OSD	languages: English, others
Image Processing	Defective Pixel Correction (DPC), sharpening
Remote control	Yes (COAX protocol)

IR LED

LED Number	1
Range	30 m
Smart IR	yes (software support)

INTERFACES

Video Output	BNC, 1.0 Vp-p, 75 Ohm
--------------	-----------------------

INSTALLATION PARAMETERS

Dimensions (mm)	95 (Ø) x 83 (H)
Weight	0.4 kg
Degree of Protection	IP 67 (details in the user's manual)
Enclosure	vandalproof, aluminium, white
Power Supply	12 VDC
Power Consumption	1 W • 4 W (IR illuminator on)



Vandal Proof AHD Multistandard Camera **NHDC-2VE-6101-II**

Operating Temperature	-30°C ~ 50°C
Humidity	max. 90%, relative (non-condensing)

