


4 MPX IP Camera with video content analysis based on Deep Learning

NVIP-4H-6502M/F-II/7043



KEY FEATURES



Lens: motorized, auto-focus function, f=2.8 ~ 12 mm/F1.3
Human/Vehicle Object Classification
D/N function - IR cut filter
Video content analysis based on Deep Learning
microSD card support
Min. Illumination: 0.003 lx (0 lx, IR on)
IR LED, range up to 50 m

DIMENSIONS



220 mm



The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

IMAGE	
Image Sensor	4 MPX CMOS sensor 1/3" SmartSens
Number of Effective Pixels	2688 (H) x 1520 (V)
Min. Illumination	0.003 lx/F1.3 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto: 1/2 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1/2 s
Wide Dynamic Range (WDR)	yes 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
LENS	
Lens Type	motorized, f=2.8 ~ 12 mm/F1.3
DORI	
DORI (Detection, Observation, Recognition, Identification)	for f = 2.8mm - D: 58.91m, O: 23.56m, R: 11.78m, I: 5.89m • for f = 12mm - D: 205.99m, O: 82.4m, R: 41.2m, I: 20.6m
DAY/NIGHT	
Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 120 s
Switching Schedule	yes
Visible Light Sensor	yes
NETWORK	
Stream Resolution	2560 x 1440 (QHD), 2592 x 1520, 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA), 480 x 240
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711
Number of Simultaneous Connection	nsmax. 10
Bandwidth	50 Mb/s in total



4 MPX IP Camera with video content analysis based on Deep Learning NVIP-4H-6502M/F-II/7043

Network Protocols Support	HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, RTMP HTTP POST
Camera Configuration	from Internet Explorer, Chrome, Opera, Safari browser • languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	SuperLive Plus (iPhone, Android)
VIDEO ANALYTICS	
Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, zone exit, object counting, face detection*, detection of people not wearing masks, pedestrian detection, cross counting, hear map, scene change, video blurred, video color cast, objects distinguishing, people counting, vehicle counting, intrusion detection, video metadata
OTHER FUNCTIONS	
Privacy Zones	4 video mask type: single color or 4 video mask type: mosaic
Motion Detection	yes
Region of interest (ROI)	8
Image Processing	90° image rotation, 180° image rotation, sharpening, mirror effect, corridor mode, vertical flip, horizontal flip, lens distortion correction
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card
Restoring default settings	via web browser, using reset button, via NMS IPTool software
	-
LED Number	3
Range	50 m
Smart IR	yes (software support)
INTERFACES	
Audio Input/Output	1 x Jack (3.5 mm)/-
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
INSTALLATION PARAMETERS	
Dimensions (mm)	with bracket: 81 (W) x 81 (H) x 220 (L)
Dimensions (mm) Weight	with bracket: 81 (W) x 81 (H) x 220 (L) 0.66 kg
. ,	
Weight	0.66 kg
Weight Degree of Protection	0.66 kg IP 67 (details in the user's manual) aluminium, white, fully cable managed wall mount bracket in-set
Weight Degree of Protection Enclosure	0.66 kg IP 67 (details in the user's manual) aluminium, white, fully cable managed wall mount bracket in-set included , IK10 impact rating • enclosure type: 4H-B
Weight Degree of Protection Enclosure Power Supply	0.66 kg IP 67 (details in the user's manual) aluminium, white, fully cable managed wall mount bracket in-set included , IK10 impact rating • enclosure type: 4H-B 12 VDC, PoE (IEEE 802.3af, Klasa 3)
Weight Degree of Protection Enclosure Power Supply Surge protection	0.66 kg IP 67 (details in the user's manual) aluminium, white, fully cable managed wall mount bracket in-set included , IK10 impact rating • enclosure type: 4H-B 12 VDC, PoE (IEEE 802.3af, Klasa 3) TVS 4000 V





4 MPX IP Camera with video content analysis based on Deep Learning NVIP-4H-6502M/F-II/7043

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name). Video metadata - video analysis function available on cameras with software version newer or equal to 5.1.2(42545).

