




## NOVUS MANAGEMENT SYSTEM AC computer unit

### NMS AC 3-R-III



#### DIMENSIONS



Unit with the Microsoft Windows 10 IoT operating system and NOVUS MANAGEMENT SYSTEM AC software installed. Designed to work as a server or server/client station. Adapted to 24/7 operation.

#### DISPLAY

|                 |                                               |
|-----------------|-----------------------------------------------|
| Monitor outputs | 1 x HDMI, 1 x Display Port, 1 x Dual link-DVI |
| Max resolution  | 3 x 4K UltraHD                                |

#### AUDIO

|              |                                             |
|--------------|---------------------------------------------|
| Audio inputs | 1 x line (3,5mm), 1 x microphone (3,5mm)    |
| Audio output | 1 x line(3,5mm), 1 x HDMI, 1 x Display Port |

#### NETWORK

|                   |                                                         |
|-------------------|---------------------------------------------------------|
| Network interface | 1 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s       |
| Przepustowość     | Max network throughput: 350Mbit/s for each network card |

#### ADDITIONAL INTERFACES

|           |                                                        |
|-----------|--------------------------------------------------------|
| USB ports | 4 x USB 2.0, 4 x USB 3.2, 1 x USB 3.2 Type-C x USB 3.0 |
|-----------|--------------------------------------------------------|

#### OPERATING SYSTEM

|                  |                                             |
|------------------|---------------------------------------------|
| Operating system | Microsoft Windows 10 IoT                    |
| System language  | Polish, English, Russian, Hungarian, others |

#### INTEGRATION

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dedicated for      | NOVUS MANAGEMENT SYSTEM AC                                                                                                                                                                                                                                                                                                                                                                                                  |
| Integrated devices | KDH-KS3012-IP, KDH-KS3024-IP, KDH-KS2000-IP-ELV, KDH-KS3000-IP-ELV, KDH-CADM500-FP, KDH-KZ3000FP-IP-M, KDH-KZ3000FP-IP-U, KDH-KZ3000-IP-M, KDH-KZ3000-IP-U, KDH-TA500CFP-IP-U/M/D, KDH-TA500C-IP-U/M/D, NOVUS IP cameras of the 4000/6000/8000 series, NOVUS IP recorders of the 4000/6000 series, NOVUS 4000 series multistandard recorders, ONVIF / RTSP IP cameras, NMS IP Recorders, NOVUS MANAGEMENT SYSTEM AC Servers |

#### INSTALLATION PARAMETERS

|                       |                                  |
|-----------------------|----------------------------------|
| Dimensions (mm)       | 427 (W) x 177 (H) x 500 (D)      |
| Weight                | 20 kg                            |
| Power supply          | Built in 700W, with 230VAC input |
| Operating Temperature | 5°C ~ 35°C                       |
| RACK Mount 19"        | 4U                               |

