



## EntraPass computer unit KT CLIENT PRO R-III



### DIMENSIONS



### DISPLAY

|                 |                                               |
|-----------------|-----------------------------------------------|
| Monitor outputs | 2 x HDMI, 2 x Display Port, 2 x Dual link-DVI |
| Max resolution  | 6 x 4K UltraHD                                |

### AUDIO

|              |                                             |
|--------------|---------------------------------------------|
| Audio inputs | 1 x line (3,5mm), 1 x microphone (3,5mm)    |
| Audio output | 1 x line(3,5mm), 2 x HDMI, 2 x Display Port |

### NETWORK

|               |                                                         |
|---------------|---------------------------------------------------------|
| Przepustowość | Max network throughput: 350Mbit/s for each network card |
|---------------|---------------------------------------------------------|

### ADDITIONAL INTERFACES

|           |                                                        |
|-----------|--------------------------------------------------------|
| USB ports | 4 x USB 2.0, 4 x USB 3.2, 1 x USB 3.2 Type-C x USB 3.0 |
|-----------|--------------------------------------------------------|

### OPERATING SYSTEM

|                  |                                             |
|------------------|---------------------------------------------|
| Operating system | Microsoft Windows 10 Pro                    |
| System language  | Polish, English, Russian, Hungarian, others |

### INTEGRATION

|                    |                                          |
|--------------------|------------------------------------------|
| Dedicated for      | EntraPass                                |
| Integrated devices | Kantech controllers KT-1, KT-400, KT-300 |

### INSTALLATION PARAMETERS

|                       |                                  |
|-----------------------|----------------------------------|
| Dimensions (mm)       | 483 (W) x 177 (H) x 505 (D)      |
| Weight                | 25 kg                            |
| Power supply          | Built in 700W, with 230VAC input |
| Operating Temperature | 5°C ~ 35°C                       |
| RACK Mount 19"        | 4U                               |