

4 MPX IP Camera with video content analysis and active deterrence

## NVIP-4H-6702M/FWLAD



## **KEY FEATURES** DUO light ( IK10 **1**265+ ..... Δ 🗮 D/N 0.02 (IR-cut Lux f=2.8~12 40 m

Resolution: 4 MPX
+Lens: motorized, auto-focus function, f=2.8 $\sim$ 12 mm/F1.4
<ul> <li>active deterrence</li> </ul>
<ul> <li>D/N function - IR cut filter</li> </ul>
<ul> <li>Video content analysis based on Deep Learning</li> </ul>
<ul> <li>microSD card support</li> </ul>
<ul> <li>WDR with double scan sensor</li> </ul>
•two-way audio
<ul> <li>Min. Illumination: 0.023 lx (0 lx, IR on)</li> </ul>
<ul> <li>IR LED, range up to 40 m</li> </ul>
<ul> <li>white LED illuminator, range up to 40 m</li> </ul>

DIMENSIONS



The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

IMAGE	
Image Sensor	4 MPX CMOS sensor 1/2.9" SmartSens
Number of Effective Pixels	2696 (H) x 1528 (V)
Min. Illumination	0.023 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto: 1/3 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1/3 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
LENS	
Lens Type	motorized, f=2.8 ~ 12 mm/F1.4
Auto-focus	zoom trigger, day/night mode trigger, manual trigger
DORI	
DORI (Detection, Observation, Recognition, Identification)	for f = 2.8mm - D: 60.09m, O: 24.03m, R: 12.01m, I: 6m • for f = 12mm - D: 175.72m, O: 70.28m, R: 35.14m, I: 17.57m
DAY/NIGHT	
Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 120 s
Switching Schedule	yes
NETWORK	
Stream Resolution	2560 x 1440 (QHD), 2592 x 1520, 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 352 x 288 (CIF), 480 x 240
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711







## 4 MPX IP Camera with video content analysis and active deterrence NVIP-4H-6702M/FWLAD

Bandwidth	30 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, HTML5, RTMP
Camera Configuration	from Internet Explorer, Chrome, Opera, Safari browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	SuperLive Plus (iPhone, Android)
VIDEO ANALYTICS	
Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, zone exit, object counting, face detection, detection of people not wearing masks, cross counting, heat map, scene change video blurred, video color cast, objects distinguishing, people counting, vehicle counting, intrusion detection, target counting by area, video metadata
OTHER FUNCTIONS	
Privacy Zones	4 video mask type: single color or 4 video mask type: mosaic
Motion Detection	yes
Region of interest (ROI)	8
Image Processing	90° image rotation, 180° image rotation, sharpening, mirror effect, corridor mode, vertical flip, horizontal flip, lens distortion correction
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card
Determent	red and blue LEDs, flashing light, • built-in speaker (predefined or custom voice messages)
Restoring default settings	via web browser, using reset button, via NMS IPTool software
IR LED	
LED Number	1
Range	40 m
Smart IR WHITE LIGHT ILLUMINATOR	yes (software support)
LED Number	1, warm white color
Range	40 m
Smart Light	yes (software support)
INTERFACES	
Audio Input/Output	1 x Jack (3.5 mm)/1 x Jack (3.5 mm) • built-in microphone/speaker
Alarm Input/Output	1 (NO/NC)/1 relay type (max. 12VDC/300mA)
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
INSTALLATION PARAMETERS	
	with bracket: 81 (W) x 81 (H) x 220 (L)
Dimensions (mm)	

IP 66 (details in the user's manual)



Degree of Protection



## 4 MPX IP Camera with video content analysis and active deterrence NVIP-4H-6702M/FWLAD

Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included , IK10 impact rating • enclosure type: 4H-B
Power Supply	12 VDC, PoE (IEEE 802.3af, Klasa 3)
Surge protection	TVS 4000 V
Power Consumption	6 W • 10 W (IR illuminator on) • 9 W (white light illuminator on) • 11 W (IR illuminator and active deterrence functions enabled)
Operating Temperature	-30°C ~ 60°C
Humidity	max. 95%, relative (non-condensing)

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).

