


2 MPX Speed Dome IP Camera with intelligent object tracking

NVIP-2SD-6540/15

6000 VSS
IP



KEY FEATURES



- Resolution: 2 MPX
- Lens: motorized varifocal, AI and AF function, optical zoom 15x, f=5 ~ 75 mm/F1.6 ~ 2.8
- D/N function - IR cut filter
- Auto Tracking
- Video content analysis based on Deep Learning
- microSD card support
- WDR with double scan sensor
- Min. Illumination from 0.00025 lx (0 lx, IR on)
- IR LED, range up to 200 m (depends on current optical zoom value)

DIMENSIONS

The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the **DOWNLOADABLE FILES** tab.

IMAGE

Image Sensor	2 MPX CMOS sensor 1/2.8" SmartSens
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.00125 lx/F1.6 - color mode • 0.00025 lx/F1.6 - B/W mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto: 1 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 128dB
Digital Noise Reduction (DNR)	2D, 3D
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

LENS

Optical Zoom	15x
Lens Type	motorized, auto-iris function, f=5 ~ 75 mm/F1.6 ~ F2.8
Auto-focus	zoom trigger, day/night mode trigger, manual trigger


DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Schedule	yes
Visible Light Sensor	yes

NETWORK

Stream Resolution	1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 352 x 288 (CIF), 480 x 240
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/-
Number of Simultaneous Connections	max. 10
Bandwidth	40 Mb/s in total

2 MPX Speed Dome IP Camera with intelligent object tracking NVIP-2SD-6540/15



Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, HTML5
Camera Configuration	from Internet Explorer, Edge, Firefox, Chrome, Opera browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	SuperLive Plus (iPhone, Android)

PTZ

Preset Commands	360 including 21 special (function) presets
Tours	8 (up to 16 presets per tour)
Patterns	4 (max. 180 s for each pattern)
Tilt/Pan Range	-10° ~ 90°/360° (continuous)
Pan/Tilt Speed	up to 80°/s (proportional to zoom)
Preset Speed	up to 80°/s

VIDEO ANALYTICS

Functions	tamper, line cross, zone entrance, zone exit, scene change, video blurred, video color cast, objects distinguishing, objects tracking, intrusion detection
-----------	--

OTHER FUNCTIONS

Privacy Zones	4 video mask type: single color
Motion Detection	yes
Image Processing	vertical flip, horizontal flip
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, object tracking
Restoring default settings	via web browser, using reset button, via NMS IPTool software

IR LED

LED Number	6
Range	up to 200 m (depends on current optical zoom value)
Smart IR	yes (hardware support)

INTERFACES

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB

INSTALLATION PARAMETERS

Dimensions (mm)	173 (Φ) x 268 (H) with bracket: 173 (W) x 415 (H) x 300 (L)
Weight	2.1 kg with bracket: 2.8 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, IK10 impact rating, In set: outdoor housing (integrated with the camera), wall mount bracket • Enclosure type: 6SD-M
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Surge protection	TVS 6000 V
Power Consumption	8 W • 12 W (IR illuminator on)



2 MPX Speed Dome IP Camera with intelligent object tracking

NVIP-2SD-6540/15

Operating Temperature	-30°C ~ 65°C
Cold start temperature	-20°C
Humidity	max. 90%, relative (non-condensing)

