

## 4 MPX IP Camera with video content analysis and active deterrence

**NVIP-4H-6711/FWLAD**

**6000** VSS  
IP



### KEY FEATURES



- Resolution: 4 MPX
- Lens: fixed focal, f=2.8 mm/F1.6
- active deterrence
- D/N function - IR cut filter
- Video content analysis based on Deep Learning
- microSD card support
- WDR with double scan sensor
- two-way audio
- Min. Illumination: 0.03 lx (0 lx, IR on)
- IR LED, range up to 40 m
- white LED illuminator, range up to 40 m

### DIMENSIONS

The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the **DOWNLOADABLE FILES** tab.

### IMAGE

|                                          |                                                     |
|------------------------------------------|-----------------------------------------------------|
| Image Sensor                             | 4 MPX CMOS sensor 1/2.9" SmartSens                  |
| Number of Effective Pixels               | 2696 (H) x 1528 (V)                                 |
| Min. Illumination                        | 0.03 lx/F1.6 - color mode • 0 lx (IR on) - B/W mode |
| Electronic Shutter                       | auto: 1/3 s ~ 1/100000 s                            |
| Digital Slow Shutter (DSS)               | up to 1/3 s                                         |
| Wide Dynamic Range (WDR)                 | yes (double scan sensor), 120dB                     |
| Digital Noise Reduction (DNR)            | 2D, 3D                                              |
| Defog Function (F-DNR)                   | yes                                                 |
| Highlight Compensation (HLC)             | yes                                                 |
| Back Light Compensation (BLC)            | yes                                                 |
| Reduction of image flicker (Antiflicker) | yes                                                 |

### LENS

|           |                            |
|-----------|----------------------------|
| Lens Type | fixed focal, f=2.8 mm/F1.6 |
|-----------|----------------------------|

### DORI

|                                                            |                                                           |
|------------------------------------------------------------|-----------------------------------------------------------|
| DORI (Detection, Observation, Recognition, Identification) | for f = 2.8mm - D: 59.66m, O: 23.86m, R: 11.93m, I: 5.96m |
|------------------------------------------------------------|-----------------------------------------------------------|

### DAY/NIGHT

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Mode                       | day/night switching: mechanical IR cut filter |
| Switching Mode             | auto, manual, time                            |
| Switching Level Adjustment | yes                                           |
| Switching Delay            | 2 ~ 120 s                                     |
| Switching Schedule         | yes                                           |

### NETWORK

|                                    |                                                                                                                                             |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Stream Resolution                  | 2560 x 1440 (QHD), 2592 x 1520, 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 352 x 288 (CIF), 480 x 240 |
| Frame Rate                         | 30 fps for each resolution                                                                                                                  |
| Multistreaming Mode                | number of streams: 3                                                                                                                        |
| Video/Audio Compression            | H.264, H.264+, H.265, H.265+, MJPEG/G.711                                                                                                   |
| Number of Simultaneous Connections | max. 10                                                                                                                                     |



## 4 MPX IP Camera with video content analysis and active deterrence

### NVIP-4H-6711/FWLAD

|                           |                                                                                                                                        |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Bandwidth                 | 30 Mb/s in total                                                                                                                       |
| Network Protocols Support | HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, HTML5, RTMP |
| Camera Configuration      | from Internet Explorer, Chrome, Opera, Safari browser • languages: Polish, English, and others                                         |
| Compatible Software       | NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000                                                                |
| Mobile applications       | SuperLive Plus (iPhone, Android)                                                                                                       |

#### VIDEO ANALYTICS

|           |                                                                                                                                                                                                                                                                                                                                                                     |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Functions | tamper, abandoned object, object disappearance, line cross, zone entrance, zone exit, object counting, face detection, detection of people not wearing masks, cross counting, heat map, scene change, video blurred, video color cast, objects distinguishing, people counting, vehicle counting, intrusion detection, counting objects in the area, video metadata |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### OTHER FUNCTIONS

|                                 |                                                                                                                                               |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Privacy Zones                   | 4 video mask type: single color or 4 video mask type: mosaic                                                                                  |
| Motion Detection                | yes                                                                                                                                           |
| Region of interest (ROI)        | 8                                                                                                                                             |
| Image Processing                | 90° image rotation, 180° image rotation, sharpening, mirror effect, corridor mode, vertical flip, horizontal flip, lens distortion correction |
| Prealarm/Postalarm              | up to 6 s/up to 120 s                                                                                                                         |
| System Reaction to Alarm Events | e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card                                                             |
| Determent                       | red and blue LEDs, flashing light, • built-in speaker (predefined or custom voice messages)                                                   |
| Restoring default settings      | via web browser, using reset button, via NMS IPTool software                                                                                  |

#### IR LED

|            |                        |
|------------|------------------------|
| LED Number | 1                      |
| Range      | 40 m                   |
| Smart IR   | yes (software support) |

#### WHITE LIGHT ILLUMINATOR

|             |                        |
|-------------|------------------------|
| LED Number  | 1, warm white color    |
| Range       | 40 m                   |
| Smart Light | yes (software support) |

#### INTERFACES

|                    |                                                                   |
|--------------------|-------------------------------------------------------------------|
| Audio Input/Output | 1 x Jack (3.5 mm)/1 x Jack (3.5 mm) • built-in microphone/speaker |
| Alarm Input/Output | 1 (NO/NC)/1 relay type (max. 12VDC/300mA)                         |
| Network Interface  | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s                     |
| Memory Card Slot   | microSD - capacity up to 256GB                                    |

#### INSTALLATION PARAMETERS

|                      |                                         |
|----------------------|-----------------------------------------|
| Dimensions (mm)      | with bracket: 81 (W) x 81 (H) x 220 (L) |
| Weight               | 0.7 kg                                  |
| Degree of Protection | IP 66 (details in the user's manual)    |
| Power Supply         | 12 VDC, PoE (IEEE 802.3af, Class 3)     |



## 4 MPX IP Camera with video content analysis and active deterrence

### **NVIP-4H-6711/FWLAD**

|                       |                                                                                                                                  |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Surge protection      | TVS 4000 V                                                                                                                       |
| Power Consumption     | 5 W • 9 W (IR illuminator on) • 9 W (white light illuminator on) • 11 W (IR illuminator and active deterrence functions enabled) |
| Operating Temperature | -30°C ~ 60°C                                                                                                                     |
| Humidity              | max. 95%, relative (non-condensing)                                                                                              |

*The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).*

