NOVUS

5 MPX IP camera with Deep Learning-based image analysis and active deterrence

NVIP-5H-4511/FWLAD





KEY FEATURES































•Lens: fixed focal, f=2.8 mm/F1.0

- •active deterrence
- •D/N function IR cut filter
- •Video content analysis based on Deep Learning
- •Licence plate recognition (LPR)
- •microSD card support
- •WDR with double scan sensor
- •two-way audio
- •Min. Illumination: 0.002 lx (0 lx, IR on)
- •IR LED, range up to 25 m
- •white LED illuminator, range up to 20 m
- "Two way power" when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

COMPLIANCE



DIMENSIONS

The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

IMAGE

Image Sensor	5 MPX CMOS sensor 1/2.7" SmartSens
Number of Effective Pixels	2880 (H) x 1620 (V)
Min. Illumination	0.002 lx/F1.0 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes (double scan sensor)
Digital Noise Reduction (DNR)	2D, 3D
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

LENS

Lens Tyne

Lens Type	11XCu 10Cu1, 1—2.0 11111/1 1.0	
DORI		
DORI (Detection, Observation, Recognition, Identification)	for f = 2.8mm - D: 56m, O: 22.4m, R: 11m, I: 5.6m	

fixed focal f=2.8 mm/F1.0

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Delay	1 ~ 36 s

NETWORK

METWORK	
Stream Resolution	2880 x 1620, 2560 x 1440 (QHD), 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3 (main stream, sub stream, third stream)
Video/Audio Compression	H.264, H.264+, H.265, H.265+/G.711
Number of Simultaneous Conne	ectionsmax. 3 connections, (max. 40 streams in total)
Bandwidth	30 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, SMTP, P2P, HTML5
ONVIF Protocol Support	Profile G/S/T/M



NOVUS





71 mm (Ø)





150 mm

5 MPX IP camera with Deep Learning-based image analysis and active deterrence NVIP-5H-4511/FWLAD

	languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC
Mobile applications	ipGO 4 (iPhone, Android)
VIDEO ANALYTICS	
Functions	abandoned object, object disappearance, line cross, zone entrance, zone exit, zone violation, multi loiter, face detection, pedestrian detection, cross counting, heat map, queue length detection, objects distinguishing, vehicle detection, intrusion detection, target counting by area, smart motion detection with objects distinguishing
OTHER FUNCTIONS	
Security	video encryption, HTTPS support, MAC/IP address filtering, force change of default password
Privacy Zones	4 video mask type: single color
Motion Detection	yes
Region of interest (ROI)	8
Audio Detection	yes
Image Processing	180° image rotation, corridor mode, vertical flip, horizontal flip
Prealarm/Postalarm	up to 5 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, saving in the cloud storage, push notification, active deterrent functions
Determent	white LEDs, steady/flashing light, red and blue LEDs, flashing light, • audio signaling device (siren), built-in speaker (custom voice messages)
Restoring default settings	via web browser, using reset button
LICENCE PLATE RECOGNITION	(LPR)
Autonomous operation mode	yes - recognition function implemented in the camera
Capacity of License Plate Database	up to 10000 license plates, on all lists.
Types of recognized number plates	all countries of the European Union
Data recorded in the camera base	recognition date/time, number of recognised licence plate, image of recognised licence plate, presence on the "white list" or "black list"
Reactions for the licence plate recognition	e-mail with attachment, saving file on FTP server, saving a file in the cloud
IR LED	
LED Number	1
Range	25 m
Smart IR	yes (hardware support)
WHITE LIGHT ILLUMINATOR	
LED Number	2, warm white color
Range	20 m
Smart Light	yes (hardware support)
INTERFACES	

1 x Ethernet - RJ-45 interface, 10/100 Mbit/s



Network Interface



5 MPX IP camera with Deep Learning-based image analysis and active deterrence NVIP-5H-4511/FWLAD

Memory Card Slot microSD - capacity up to 256GB

INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 71 (Φ) x 150 (L)
Weight	0.36 kg
Degree of Protection	IP 67 (details in the user's manual)
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Surge protection	TVS 4000 V
Power Consumption	2.1 W • 3.4 W (IR illuminator on) • 4.6 W (white light illuminator on) • 6 W (active deterrence functions enabled)
Operating Temperature	-35°C ~ 60°C
Humidity	max. 95%, relative (non-condensing)

