8-channel IP Recorder

NVR-6208P8-H1-II



KEY FEATURES

- 8 x PoE Ethernet ports
- 8 x video and audio channels
- Recording speed up to 240 fps at 3200 x 1800
- Supports resolution up to 3200 x 1800
- Recorded stream size: 64 Mb/s in total from all cameras
- 1 x internal place for HDD mounting
- 2 x monitor outputs (HDMI, VGA)
- Intelligent image analysis

COMPLIANCE

DIMENSIONS

The recorder is dedicated to work with NOVUS 6000 series IP cameras. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

The recorder need 1.4.10 firmware version to support 6Mpx IP cameras.

VIDEO

IP Cameras	up to 8 channels at 3200 x 1800 resolution (video + audio)
Maximum Supported Camera Resolution	3200 x 1800
Compression	H.264, H.265, H.265+, H.265 Smart
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA (up to 2 monitors simultaneously)
Dualstreaming Support	yes
Fisheye Support	yes, 6000 IP series cameras • using any web browser, ipGO 6, N Control 6000

AUDIO

Audio Input/Output	- / 1 x HDMI

RECORDING

Stream Size	64 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, alarm input, motion detection, intelligent image analysis functions
Prealarm/Postalarm	up to 5 s/up to 600 s

DISPLAY

Display Speed	240 fps (8 x 30 fps)

PLAYBACK

Playback Speed	240 fps (8 x 30 fps for 2592 x 1944) • 240 fps (8 x 30 fps)
Recorded Data Search	by date/time, events, image analysis events, POS, motion in a defined area, tags, license plate number

BACKUP

Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	AVI, RPAS (player included)

STORAGE

Internal Storage	available mount: 1 x HDD 3.5” 24 TB SATA
Total Internal Capacity	24 TB

ALARM

Camera Alarm Input/Output	supports IP camera’s alarm input/output

8-channel IP Recorder
NVR-6208P8-H1-II







Motion Detection	supports camera's motion detection
System Reaction to Alarm Events	buzzer, alarm output activation, recording activation, PTZ, e-mail with atatchment, Full Screen, PUSH message, voice prompt, snapshot

INTELLIGENT IMAGE ANALYSIS

Supported Functions	Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance, Face Detection, Perimeter Intrusion Detection by pedestrian or vehicle, Line Cross Detection by pedestrian or vehicle, Fire detection, Temperature measurement, Video metadata

NETWORK

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s • 8 x Ethernet PoE (IEEE802.3af/at, Class 4) - RJ-45 interface, 10/100 Mbit/s, with Extended mode
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, IEEE 802.1X, PPPoE, SMTP, P2P, POS, HTML5
ONVIF Protocol Support	G/M/S/T profiles
PC/MAC Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000
Mobile applications	ipGO 6 (iPhone, Android)
Number of Simultaneous Connections	up to 64 clients, up to 12 main streams or 64 substreams or 8 playback streams in total
Bandwidth	64 Mb/s in total to all client workstations

PTZ

PTZ Functions	pan/tilt/zoom, preset commands

AUXILIARY INTERFACES

USB Ports	2 x USB 2.0

OPERATING SYSTEM

Operating System	Linux
OSD	languages: Polish, English, others
Control	PC mouse (in-set included), network
System Diagnostic	automatic control of: HDDs, network, camera connection loss
Security	password protection, IP filtering, MAC filtering, ARP guard

INSTALLATION PARAMETERS

Dimensions (mm)	255 (W) x 42 (H) x 233 (D)
Weight	0.84 kg (without HDD)
Power Supply	48 VDC (100 ~ 240 VAC/48 VDC PSU in-set included)
Power Consumption	15 W (with 1 HDD) + 72 W PoE
Operating Temperature	-10°C ~ 50°C

The availability of individual functions (including image analysis) depends on the model of the cameras used, as well as the software version of the recorder and cameras.
Presented display and playback speeds are achieved using dual-streaming. Detailed data on hard drives can be found in the compatibility table available in the DOWNLOADABLE FILES tab.
The recorder need 1.4.10 firmware version to support 6Mpx IP cameras.