NoVus

8 MPX IP Motor-zoom Camera with video content analysis based on Deep Learning

NVIP-8VE-6502M/F-II





KEY FEATURES





















- •Resolution: 8 MPX (4K Ultra HD)
- •Lens: motorized, auto-focus function, f= $2.8 \sim 12$ mm/F1.4
- Human/Vehicle Object Classification
- •D/N function IR cut filter
- •Video content analysis based on Deep Learning
- •microSD card support
- •WDR with double scan sensor
- •Min. Illumination: 0.015 lx (0 lx, IR on)
- •IR LED, range up to 50 m

DIMENSIONS



112 mm (Ø)



The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

IMAGE

| INAGE | |
|---|--|
| Image Sensor | 8 MPX CMOS sensor 1/2.8" SONY STARVIS |
| Number of Effective Pixels | 3864 (H) x 2192 (V) |
| Min. Illumination | 0.015 lx/F1.4 - color mode • 0 lx (IR on) - B/W mode |
| Electronic Shutter | auto/manual: 1/3 s ~ 1/100000 s |
| Digital Slow Shutter (DSS) | up to 1/3 s |
| Wide Dynamic Range (WDR) | yes (double scan sensor), 120dB |
| Digital Image Stabilization (DIS) | yes |
| Digital Noise Reduction (DNR) | 3D |
| Defog Function (F-DNR) | yes |
| Highlight Compensation (HLC) | yes |
| Back Light Compensation (BLC) | yes |
| Reduction of image flicker (Antiflicker) | yes |

LENS

| Lens Type | motorized, $f=2.8 \sim 12$ mm/F1.4 |
|------------|--|
| Auto-focus | zoom trigger, day/night mode trigger, manual trigger |

DORI

| DORI (Detection, Observation, | for f = 2.8mm - D: 85m, O: 34m, R: 17m, I: 8m • for f = 12mm - D: |
|-------------------------------|---|
| Recognition, Identification) | 289m, O: 116m, R: 58m, I: 29m |

DAY/NIGHT

| Mode | day/night switching: mechanical IR cut filter |
|----------------------------|---|
| Switching Mode | auto, manual, time |
| Switching Level Adjustment | yes |
| Switching Delay | 2 ~ 120 s |
| Switching Schedule | yes |
| Visible Light Sensor | yes |

NETWORK

| Stream Resolution | 3840 x 2160 (4K Ultra HD), 3072 x 2048, 2560 x 1440 (QHD), 2592 x 1520, 2592 x 1944, 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 352 x 288 (CIF), 480 x 240 |
|-------------------|--|
| Frame Rate | 30 fps for each resolution |





8 MPX IP Motor-zoom Camera with video content analysis based on Deep Learning NVIP-8VE-6502M/F-II

| Multistreaming Mode | number of streams: 3 |
|-----------------------------------|---|
| Video/Audio Compression | H.264, H.264+, H.265, H.265+, MJPEG/G.711 |
| Number of Simultaneous Connection | smax. 10 |
| Bandwidth | 82 Mb/s in total |
| Network Protocols Support | HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, SSL/TLS, HTML5, RTMP |
| Camera Configuration | from Internet Explorer, Edge, Firefox, Chrome, Opera, Safari browser • languages: Polish, English, and others |
| Compatible Software | NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000 |
| Mobile applications | SuperLive Plus (iPhone, Android) |
| VIDEO ANALYTICS | |
| Functions | tamper, abandoned object, object disappearance, line cross, zone entrance, zone exit, object counting, loiter, multi loiter, face detection, detection of people not wearing masks, cross counting, heat map, scene change, video blurred, video color cast, objects distinguishing, people counting, vehicle counting, intrusion detection, target counting by area, video metadata, illegal parking detection |
| OTHER FUNCTIONS | |
| Security | video encryption, configuration encryption, IEEE 802.1X support, HTTPS support, Basic authorization for HTTP/RTSP, Digest authorization for HTTP/RTSP, MAC/IP address filtering, force change of default password |
| Privacy Zones | 4 video mask type: single color or 4 video mask type: mosaic |
| Motion Detection | yes |
| Region of interest (ROI) | 8 |
| Audio Detection | yes |
| Image Processing | 90° image rotation, 180° image rotation, sharpening, mirror effect, corridor mode, vertical flip, horizontal flip, lens distortion correction |
| Prealarm/Postalarm | up to 6 s/up to 120 s |
| System Reaction to Alarm Events | e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card |
| Restoring default settings | via web browser, using reset button, via NMS IPTool software |
| IR LED | |
| LED Number | 3 |
| Range | 50 m |
| Smart IR | yes (software support) |
| INTERFACES | |
| Audio Input/Output | 1 x Jack (3.5 mm)/- • built-in microphone |
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s |
| Memory Card Slot | microSD - capacity up to 256GB |
| INSTALLATION PARAMETERS | |
| Dimensions (mm) | 112 (Ф) x 100 (H) |
| Weight | 0.7 kg |
| Degree of Protection | IP 67 (details in the user's manual) |
| | |







8 MPX IP Motor-zoom Camera with video content analysis based on Deep Learning NVIP-8VE-6502M/F-II

| Enclosure | vandalproof, IK10 impact rating, aluminium, white $ullet$ enclosure type: 6VE-M |
|-----------------------|---|
| Power Supply | 12 VDC, PoE (IEEE 802.3af, Klasa 3) |
| Surge protection | TVS 4000 V |
| Power Consumption | 7 W • 11 W (IR illuminator on) |
| Operating Temperature | -30°C ~ 60°C |
| Humidity | max. 95%, relative (non-condensing) |

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).

