

Electric strike

BIRA-S12R



Electric strike (NO), low-current. For remote wired opening of doors, gates, flaps, furniture. It can be used in steel, aluminum, wooden and PVC profiles, both internal and external, with the possibility of assembly for left and right doors as well as in vertical and horizontal position. Adjusting the hook in the range of 4mm facilitates assembly and ensures precise adjustment of the electric strike to the handle lock.

Possibility of assembly together with fixing plates:

OK-P2 - Flat plate, short, galvanized (130x25x3mm)

OK-P5 - Flat plate, long, galvanized (250x25x3mm)

OK-K1 - Flat plate, short with slip, made of stainless steel (130x25x3mm)

OK-K4 - Angular, long, right, galvanized steel (250x25 / 32x3mm)

OK-K2 - Angular plate, long, left, galvanized (250x25 / 32x3mm)

Explanation of the letters used in the symbols of electric strikes:

S- fail-secure

R- fail-safe

M- with microswitch

P- with memory

Lock type	without supply normally open (NO)
-----------	-----------------------------------

power consumption	190 mA
-------------------	--------

Producer	BIRA
----------	------

power	12V DC
-------	--------

dimensions	75 x 20.5 x 28.5
------------	------------------

Maximal pressure on the electrocracker	350Kg
--	-------

Additional functions	fail-safe, low-current
----------------------	------------------------