NoVus

6 MPX Vandal Proof IP Camera with Fisheye Lens

NVIP-6F-6501





KEY FEATURES























- •Resolution: 6 MPX
- •Lens: fisheye, f=1.65 mm/F2.0
- $\bullet \mbox{active ambient noise cancellation}$
- •D/N function IR cut filter
- •Video content analysis based on Deep Learning
- •microSD card support
- •WDR with double scan sensor
- •two-way audio
- •Min. Illumination from 0.01 lx (0 lx, IR on)
- •IR LED, range up to 20 m

COMPLIANCE



DIMENSIONS





The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the $\ensuremath{\mathsf{DOWNLOADABLE}}$ FILES tab.

IMAGE

Image Sensor	6 MPX CMOS sensor 1/2.5" SmartSens
Min. Illumination	0.01 lx/F2.0 - color mode • 0 lx (IR on) - B/W mode
S/N Ratio	> 50 dB (AGC off)
Electronic Shutter	auto: 1/3 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1/3 s
Wide Dynamic Range (WDR)	yes 120dB
Digital Noise Reduction (DNR)	3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

LENS

Lens Type	fisheye,	f=1.65	mm/F2.0

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 6000 s
Visible Light Sensor	yes

NETWORK

METWORK		
Stream Resolution	3200 x 1800 (QHD+), 1920 x 1080 (Full HD), 2160 x 2160, 1440 x 1440, 1280 x 720 (HD), 960 x 960, 480 x 480	
Frame Rate	15 fps for other resolutions	
Multistreaming Mode	number of streams: 2 (main stream, sub stream)	
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711	
Number of Simultaneous Conne	ctionsmax. 10 connections, (max. 20 streams in total)	
Bandwidth	70 Mb/s in total	
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, P2P, HTML5, RTMP	
ONVIF Protocol Support	Profile G/S	



NoV∪s

6 MPX Vandal Proof IP Camera with Fisheye Lens NVIP-6F-6501

Camera Configuration	from Edge, Firefox, Chrome, Opera, Safari browser • languages: Polish, English, and others	
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000	
Mobile applications	ipGO 6 (iPhone, Android)	
VIDEO ANALYTICS		
Functions	line cross, zone entrance, zone exit, object counting, multi loiter, heat map, intrusion detection • image analysis functions are available when the "Ceiling" option is selected in the "Installation Method" menu	
OTHER FUNCTIONS		
Privacy Zones	4 video mask type: single color	
Motion Detection	yes	
Region of interest (ROI)	8	
Image Processing	"fisheye" view, panoramic view, "fisheye" view + 3 PTZ views, panoramic view + 3 PTZ views, 4 PTZ views, 180° image rotation, sharpening, mirror effect	
Prealarm/Postalarm	up to 6 s/up to 120 s	
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation	
Restoring default settings	via web browser, using reset button, via NMS IPTool software	
IR LED		
LED Number	4	
Range	20 m	
Smart IR	yes (hardware support)	
INTERFACES		
Video Output	BNC, 1.0 Vp-p, 75 Ohm	
Audio Input/Output	1 x Jack (3.5 mm)/1 x Jack (3.5 mm) • built-in basic microphone and noise cancellation microphone	
Alarm Input/Output	1 (NO/NC)/1 relay type (max. 12VDC/300mA)	
RS-485	yes	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s	
Memory Card Slot	microSD - capacity up to 256GB	
INSTALLATION PARAMETERS		
Dimensions (mm)	130 (Ф) x 46 (H)	
Weight	0.55 kg	
Degree of Protection	IP 67 (details in the user's manual)	
Enclosure	vandalproof, IK10 impact rating, aluminium, white • enclosure type: 6F	
Power Supply	12 VDC, PoE (IEEE 802.3af, Klasa 3)	
Surge protection	TVS 4000 V	
Power Consumption	5 W • 10 W (IR illuminator on)	
Operating Temperature	-30°C ~ 60°C	



