




NOVUS MANAGEMENT SYSTEM AC computer unit

NMS AC CLIENT 5-R-IV



DIMENSIONS



Unit with the Microsoft Windows 11 Pro operating system and the NOVUS MANAGEMENT SYSTEM AC software installed. Designed to work as a client. Adapted to 24/7 operation.

DISPLAY

Monitor outputs	1 x HDMI, 1 x Display Port, 1 x Dual link-DVI
Max resolution	3 x 4K UltraHD

AUDIO

Audio inputs	1 x line (3,5mm), 1 x microphone (3,5mm)
Audio output	1 x line(3,5mm), 1 x HDMI, 1 x Display Port

NETWORK

Network interface	1 x Ethernet - złącze RJ45, 10/100/1000/2500 Mbit/s
Przepustowość	Max network throughput: 500Mbit/s for each network card

ADDITIONAL INTERFACES

USB ports	5 x USB 3.2, 2 x USB 2.0, 1 x USB 3.2 Type-C x USB 3.0
-----------	--

OPERATING SYSTEM

Operating system	Microsoft Windows 11 Pro
System language	Polish, English, Hungarian, others

INTEGRATION

Dedicated for	NOVUS MANAGEMENT SYSTEM AC
Integrated devices	NOVUS MANAGEMENT SYSTEM AC Servers

INSTALLATION PARAMETERS

Dimensions (mm)	427 (W) x 177 (H) x 500 (D)
Weight	20 kg
Power supply	Built in 700W, with 230VAC input
Operating Temperature	5°C ~ 35°C
RACK Mount 19"	4U
Loops (per Gateway)	10
Cards	3000
Cards type	any technology compatible with the reader
Access level	250/loop
Schedule	20
Holidays	366/gateway dni
Anti-Passback	local





NOVUS MANAGEMENT SYSTEM AC computer unit NMS AC CLIENT 5-R-IV

Latch mode	yes
Reports	filtered, save in xls format
Multi-card access	yes
alarm reset	manually
LPR Zones	yes
Global interlock	yes

