



# NOVUS MANAGEMENT SYSTEM AC computer unit

## NMS AC CLIENT 5-R-IV



### DIMENSIONS



Unit with the Microsoft Windows 11 Pro operating system and the NOVUS MANAGEMENT SYSTEM AC software installed. Designed to work as a client. Adapted to 24/7 operation.

### DISPLAY

|                 |                                               |
|-----------------|-----------------------------------------------|
| Monitor outputs | 1 x HDMI, 1 x Display Port, 1 x Dual link-DVI |
| Max resolution  | 3 x 4K UltraHD                                |

### AUDIO

|              |                                             |
|--------------|---------------------------------------------|
| Audio inputs | 1 x line (3,5mm), 1 x microphone (3,5mm)    |
| Audio output | 1 x line(3,5mm), 1 x HDMI, 1 x Display Port |

### NETWORK

|                   |                                                         |
|-------------------|---------------------------------------------------------|
| Network interface | 1 x Ethernet - złącze RJ45, 10/100/1000/2500 Mbit/s     |
| Przepustowość     | Max network throughput: 500Mbit/s for each network card |

### ADDITIONAL INTERFACES

|           |                                                        |
|-----------|--------------------------------------------------------|
| USB ports | 5 x USB 3.2, 2 x USB 2.0, 1 x USB 3.2 Type-C x USB 3.0 |
|-----------|--------------------------------------------------------|

### OPERATING SYSTEM

|                  |                                    |
|------------------|------------------------------------|
| Operating system | Microsoft Windows 11 Pro           |
| System language  | Polish, English, Hungarian, others |

### INTEGRATION

|                    |                                    |
|--------------------|------------------------------------|
| Dedicated for      | NOVUS MANAGEMENT SYSTEM AC         |
| Integrated devices | NOVUS MANAGEMENT SYSTEM AC Servers |

### INSTALLATION PARAMETERS

|                       |                                           |
|-----------------------|-------------------------------------------|
| Dimensions (mm)       | 427 (W) x 177 (H) x 500 (D)               |
| Weight                | 20 kg                                     |
| Power supply          | Built in 700W, with 230VAC input          |
| Operating Temperature | 5°C ~ 35°C                                |
| RACK Mount 19"        | 4U                                        |
| Loops (per Gateway)   | 10                                        |
| Cards                 | 3000                                      |
| Cards type            | any technology compatible with the reader |
| Access level          | 250/loop                                  |
| Schedule              | 20                                        |
| Holidays              | 366/gateway dni                           |
| Anti-Passback         | local                                     |





## NOVUS MANAGEMENT SYSTEM AC computer unit **NMS AC CLIENT 5-R-IV**

|                   |                              |
|-------------------|------------------------------|
| Latch mode        | yes                          |
| Reports           | filtered, save in xls format |
| Multi-card access | yes                          |
| alarm reset       | manually                     |
| LPR Zones         | yes                          |
| Global interlock  | yes                          |

