




# NOVUS MANAGEMENT SYSTEM AC computer unit

## NMS AC 7-T-IV



### DIMENSIONS



Unit with the Microsoft Windows 10 IoT operating system and NOVUS MANAGEMENT SYSTEM AC software installed. Designed to work as a server or server/client station. Adapted to 24/7 operation.

### DISPLAY

Monitor outputs	1 x HDMI, 1 x Display Port, 1 x Dual link-DVI
Max resolution	3 x 4K UltraHD

### AUDIO

Audio inputs	1 x line (3,5mm), 1 x microphone (3,5mm)
Audio output	1 x line(3,5mm), 1 x HDMI, 1 x Display Port

### NETWORK

Network interface	2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s • 1 x Ethernet - złącze RJ45, 10/100/1000/2500 Mbit/s
Przepustowość	Max network throughput: 500Mbit/s for 10/100/1000/2500 Mbit/s network card and 350Mbit/s for 10/100/1000 Mbit/s network card

### ADDITIONAL INTERFACES

USB ports	5 x USB 3.2, 2 x USB 2.0, 1 x USB 3.2 Type-C x USB 3.0
-----------	--

### OPERATING SYSTEM

Operating system	Microsoft Windows 10 IoT
System language	Polish, English, Hungarian, others

### INTEGRATION

Dedicated for	NOVUS MANAGEMENT SYSTEM AC
Integrated devices	KDH-KS3012-IP, KDH-KS3024-IP, KDH-KS2000-IP-ELV, KDH-KS3000-IP-ELV, KDH-CADM500-FP, KDH-KZ3000FP-IP-M, KDH-KZ3000FP-IP-U, KDH-KZ3000-IP-M, KDH-KZ3000-IP-U, KDH-TA500CFP-IP-U/M/D, KDH-TA500C-IP-U/M/D, Novus IP cameras of the 4000/6000/8000 series, Novus IP recorders of the 4000/6000 series, Novus 4000 series multistandard recorders, ONVIF / RTSP IP cameras, NMS IP Recorders, NOVUS MANAGEMENT SYSTEM AC Servers, SATEL Integra control panels, Net I/O Modules LANKON-008

### INSTALLATION PARAMETERS

Dimensions (mm)	160 (W) x 410 (H) x 428 (D)
Weight	10 kg
Power supply	Built in 700W, with 230VAC input
Operating Temperature	5°C ~ 35°C

