




## NMS AC computer unit KT STATION LITE T-IV



### DIMENSIONS



Unit with the Microsoft Windows 11 Pro operating system and the latest version of Entrapass software installed. Designed to work as a client. Adapted to 24/7 operation.

### DISPLAY

|                 |   |
|-----------------|---|
| Monitor outputs | 1 x HDMI, 1 x Display Port, 1 x Dual link-DVI |
| Max resolution  | 3 x 4K UltraHD                                |

### AUDIO

|              |   |
|--------------|---|
| Audio inputs | 1 x line (3,5mm), 1 x microphone (3,5mm)    |
| Audio output | 1 x line(3,5mm), 1 x HDMI, 1 x Display Port |

### NETWORK

|                   |   |
|-------------------|---|
| Network interface | 1 x Ethernet - złącze RJ45, 10/100/1000/2500 Mbit/s     |
| Przepustowość     | Max network throughput: 500Mbit/s for each network card |

### ADDITIONAL INTERFACES

|           |  |
|-----------|--|
| USB ports | 5 x USB 3.2, 2 x USB 2.0, 1 x USB 3.2 Type-C x USB 3.0 |
|-----------|--|

### OPERATING SYSTEM

|                  |                                    |
|------------------|------------------------------------|
| Operating system | Microsoft Windows 11 Pro           |
| System language  | Polish, English, Hungarian, others |

### INTEGRATION

|                    |  |
|--------------------|--|
| Dedicated for      | EntraPass                                |
| Integrated devices | Kantech controllers KT-1, KT-400, KT-300 |

### INSTALLATION PARAMETERS

|                       |                                  |
|-----------------------|----------------------------------|
| Dimensions (mm)       | 185 (W) x 420 (H) x 450 (D)      |
| Weight                | 10 kg                            |
| Power supply          | Built in 700W, with 230VAC input |
| Operating Temperature | 5°C ~ 35°C                       |

