
# Entrapass computer unit

## KT CLIENT PRO T-IV



### DIMENSIONS




A unit with the Microsoft Windows 11 Pro operating system and the latest version of Entrapass software installed. Designed for use as a server or server/client setup. Adapted to 24/7 operation.

### DISPLAY

| | |
|---|---|
| Monitor outputs | 2 x HDMI, 2 x Display Port, 2 x Dual link-DVI |
| Max resolution | 6 x 4K UltraHD |

### AUDIO

| | |
|---|---|
| Audio inputs | 1 x line (3,5mm), 1 x microphone (3,5mm) |
| Audio output | 1 x line(3,5mm), 2 x HDMI, 2 x Display Port |

### NETWORK

| | |
|---|---|
| Network interface | 1 x Ethernet - złącze RJ45, 10/100/1000/2500 Mbit/s |
| Przepustowość | Max network throughput: 500Mbit/s for each network card |

### ADDITIONAL INTERFACES

| | |
|---|---|
| USB ports | 5 x USB 3.2, 2 x USB 2.0, 1 x USB 3.2 Type-C x USB 3.0 |

### OPERATING SYSTEM

| | |
|---|---|
| Operating system | Microsoft Windows 11 Pro |
| System language | Polish, English, Hungarian, others |

### INTEGRATION

| | |
|---|---|
| Dedicated for | EntraPass |
| Integrated devices | Kontrolery Kantech KT-1, KT-2, KT-400 oraz poprzednie generacje KT |

### INSTALLATION PARAMETERS

| | |
|---|---|
| Dimensions (mm) | 185 (W) x 420 (H) x 450 (D) |
| Weight | 10 kg |
| Power supply | Built in 700W, with 230VAC input |
| Operating Temperature | 5°C ~ 35°C |