



Entrapass computer unit

KT CLIENT STD R-IV



DIMENSIONS



A unit with the Microsoft Windows 11 Pro operating system and the latest version of Entrapass software installed. Designed for use as a server or server/client setup. Adapted to 24/7 operation.

DISPLAY

Monitor outputs	2 x HDMI, 2 x Display Port, 2 x Dual link-DVI
Max resolution	6 x 4K UltraHD

AUDIO

Audio inputs	1 x line (3,5mm), 1 x microphone (3,5mm)
Audio output	1 x line(3,5mm), 2 x HDMI, 2 x Display Port

NETWORK

Network interface	1 x Ethernet - złącze RJ45, 10/100/1000/2500 Mbit/s
Przepustowość	Max network throughput: 500Mbit/s for each network card

ADDITIONAL INTERFACES

USB ports	5 x USB 3.2, 2 x USB 2.0, 1 x USB 3.2 Type-C x USB 3.0
-----------	--

OPERATING SYSTEM

Operating system	Microsoft Windows 11 Pro
System language	Polish, English, Hungarian, others

INTEGRATION

Dedicated for	EntraPass
Integrated devices	Kontrolery Kantech KT-1, KT-2, KT-400 oraz poprzednie generacje KT

INSTALLATION PARAMETERS

Dimensions (mm)	483 (W) x 177 (H) x 505 (D)
Weight	25 kg
Power supply	Built in 700W, with 230VAC input
Operating Temperature	5°C ~ 35°C
RACK Mount 19"	4U

