NOVUS

6 MPX IP Motor-zoom Camera with video content analysis based on Deep Learning

NVIP-6H-6502M/F





KEY FEATURES





















- •Resolution: 6 MPX
- *Lens: motorized, auto-iris and auto-focus function, f=2.8 \sim 12 mm/F1.6
- Human/Vehicle Object Classification
- •D/N function IR cut filter
- •Video content analysis based on Deep Learning
- •microSD card support
- •WDR with double scan sensor
- two-way audio
- •Min. Illumination: 0.008 lx (0 lx, IR on)
- •IR LED, range up to 50 m

COMPLIANCE

DIMENSIONS





81 mm





220 mm

The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

All camera stream resolutions are supported by NVRs with firmware version 1.4.10 or higher.

IMAGE

IMAGE	
Image Sensor	6 MPX CMOS sensor 1/2.5" SmartSens
Min. Illumination	0.008 lx/F1.6 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/4 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1/4 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

LENS

Lens Type	motorized, auto-iris function, f=2.8 ~ 12 mm/F1.6
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

DORI

DORI (Detection, Observation,	for f = 2.8mm - D: 66m, O: 27m, R: 13m, I: 7m • for f = 12mm - D:
Recognition, Identification)	204m, O: 82m, R: 41m, I: 20m

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 120 s
Visible Light Sensor	yes

NETWORK

Stream Resolution	3296 x 1856, 3200 x 1800 (QHD+), 2880 x 1624, 2688 x 1520, 1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 352 x 288 (CIF), 480 x 240
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711








6 MPX IP Motor-zoom Camera with video content analysis based on Deep Learning NVIP-6H-6502M/F

Number of Simultaneous Connection	nsmax. 10
Bandwidth	62 Mb/s in total
Network Protocols Support	HTTP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, SSL/TLS, HTML5, RTMP
ONVIF Protocol Support	Profile G/S/T/M
Camera Configuration	from Internet Explorer, Edge, Firefox, Chrome, Opera, Safari browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	ipGO 6 (iPhone, Android)
VIDEO ANALYTICS	
Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, zone exit, loiter, face detection, detection of people not wearing masks, cross counting, heat map, scene change, video blurred, video color cast, objects distinguishing, people counting, vehicle counting, intrusion detection, target counting by area, video metadata, illegal parking detection
OTHER FUNCTIONS	
Security	video encryption, configuration encryption, IEEE 802.1X support, HTTPS support, Basic authorization for HTTP/RTSP, Digest authorization for HTTP/RTSP, MAC/IP address filtering, force change or default password
Privacy Zones	4 video mask type: single color or 4 video mask type: mosaic
Motion Detection	yes
Region of interest (ROI)	8
Audio Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect, corridor mode, vertical flip, horizontal flip, lens distortion correction
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation
Restoring default settings	via web browser, using reset button, via NMS IPTool software
IR LED	
LED Number	3
Range	50 m
Smart IR	yes (software support)
INTERFACES	
Audio Input/Output	1 x Jack (3.5 mm)/1 x Jack (3.5 mm) • built-in microphone
Alarm Input/Output	1 (NO/NC)/1 relay type (max. 12VDC/300mA)
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
	increase capacity up to 23005
INSTALLATION PARAMETERS	micross capacity up to 2500B
Dimensions (mm)	with bracket: 81 (W) x 81 (H) x 220 (L)
Dimensions (mm)	with bracket: 81 (W) x 81 (H) x 220 (L)







6 MPX IP Motor-zoom Camera with video content analysis based on Deep Learning NVIP-6H-6502M/F

Surge protection	TVS 4000 V
Power Consumption	6.5 W • 11 W (IR illuminator on)
Operating Temperature	-30°C ~ 60°C
Humidity	max. 95%, relative (non-condensing)

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).

