
32" LCD monitor designed for continuous operation

NVM-6032LCD



KEY FEATURES



- dedicated to continuous operation (24/7)
- anti-glare panel coating eliminating reflections
- short response time (8ms) preventing blurring of dynamic image parts
- image correction options to help you capture all the details even in difficult lighting conditions
- LED backlight

DIMENSIONS



LCD PANEL

Panel Type	IPS, LED backlight
Surface treatment	Anti-glare treatment (haze 25%), 3H hard coating
Screen Size (Diagonal)	32"
Panel Resolution	1920 x 1080
Viewable area	698.4 x 392.85 mm
Pixel pitch	0.36375 mm
Format	16:9
Brightness	350 cd/m2
Contrast Ratio	1000:1
Viewing Angle (H/V)	178°/178°
Response Time	8 ms
Refresh frequency	60 Hz (max)
Display Color	16.7 mln (gamut: sRGB: 92%, DCI-P3: 74%)

OTHER FUNCTIONS

OSD	languages: Polish, English
Digital Filter	3D
Built-in Speakers	2 x 3 W

INTERFACES

Video Input	2 x CVBS, BNC connector (loop-through), 1 x VGA, 1 x HDMI
Audio Input	1 x Mini Jack stereo, 1 x HDMI (stereo)
External Control	Infrared remote control
Other Connectivity	USB 2.0 (for service)

INSTALLATION PARAMETERS

Dimensions (mm)	738 (W) x 478 (H) x 190 (D)
Weight	4 kg
Case	black, plastic
Power Supply	100 ~ 240 VAC
Power Consumption	35 W (max) • 0.3 W (in standby mode)
Operating Temperature	+10°C ~ +45°C
Humidity	15% - 85%, relative (non-condensing)
Mounting Standard	VESA 100 x 100 mm