NoVus

6 MPX Bullet IP Camera with white light and IR illuminator

NVIP-6H-6202M/WL/7043





KEY FEATURES























- •Resolution: 6 MPX
- •Lens: motorized, auto-focus function, f=2.8 \sim 12 mm/F1.6
- MicroSD card support
- •D/N function IR cut filter
- •Video content analysis based on Deep Learning
- •microSD card support
- •WDR with double scan sensor
- •Min. Illumination from 0.008 lx
- \bullet IR LED, range up to 50 m
- •white LED illuminator, range up to 40 m

COMPLIANCE

Onvif*1000

DIMENSIONS

The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

All camera stream resolutions are supported by NVRs with firmware version 1.4.10 or higher.

IMAGE

INAGE		
Image Sensor	6 MPX CMOS sensor 1/2.5" SmartSens	
Min. Illumination	0.008 lx/F1.6 - color mode • 0 lx (IR on) - B/W mode	
Electronic Shutter	auto/manual: 1/4 s ~ 1/100000 s	
Digital Slow Shutter (DSS)	up to 1/4 s	
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB	
Digital Noise Reduction (DNR)	3D	
Highlight Compensation (HLC)	yes	
Back Light Compensation (BLC)	yes	
Reduction of image flicker (Antiflicker)	yes	

LENS

Lens Type	motorized, f=2.8 \sim 12 mm/F1.6
Auto-focus	zoom trigger, manual trigger

DORI

DORI (Detection, Observation, Recognition, Identification)	for f = 2.8mm - D: 66m, O: 27m, R: 13m, I: 7m • for f = 12mm - D: 204m, O: 82m, R: 41m, I: 20m
recognition, racinameation,	20, 0. 02, 12, 20

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Delay	2 ~ 6000 s
Switching Schedule	yes

NETWORK

Stream Resolution	3200 x 1800 (QHD+), 2688 x 1520, 1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 352 x 288 (CIF), 480 x 240
Frame Rate	30 fps for other resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711
Number of Simultaneous Connectionsmax. 6	
Bandwidth	24 Mb/s in total





NoVus





81 mm





220 mm

$6\,\text{MPX}$ Bullet IP Camera with white light and IR illuminator NVIP-6H-6202M/WL/7043

Network Protocols Support	HTTP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DDNS, NTP, RTSP, RTP UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, P2P, HTML5, RTMP, HTTP POST
ONVIF Protocol Support	Profile G/S/T
Camera Configuration	from Internet Explorer, Edge, Firefox, Chrome, Opera browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	ipGO 6 (iPhone, Android)
VIDEO ANALYTICS	
Functions	abandoned object, object disappearance, line cross, scene change, video blurred, video color cast, objects distinguishing, intrusion detection, smart motion detection with objects distinguishing
OTHER FUNCTIONS	
Privacy Zones	4 video mask type: single color
Motion Detection	yes
Region of interest (ROI)	8
Image Processing	90° image rotation, 180° image rotation, sharpening, mirror effect, corridor mode, vertical flip, horizontal flip
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card
Restoring default settings	via web browser, using reset button, via NMS IPTool software
IR LED	
LED Number	2
Range	50 m
Smart IR	yes (software support)
WHITE LIGHT ILLUMINATOR	
LED Number	1, warm white color
Range	40 m
Smart Light	yes (software support)
•	
INTERFACES Audio Input/Output	1 v lack /2 5 mm)/ a built in microphopa
Audio Input/Output	1 x Jack (3.5 mm)/- • built-in microphone
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot INSTALLATION PARAMETERS	microSD - capacity up to 256GB
Dimensions (mm)	with bracket: 81 (W) x 81 (H) x 220 (L)
Weight	0.68 kg
Degree of Protection	IP 67 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included , IK10 impact rating • enclosure type: 4H-B
Power Supply	12 VDC, PoE (IEEE 802.3af, Klasa 3)
Surge protection	TVS 4000 V



Power Consumption

6 W • 10 W (IR illuminator on) • 8 W (white light illuminator on)



6 MPX Bullet IP Camera with white light and IR illuminator ${f NVIP-6H-6202M/WL/7043}$

Operating Temperature	-30°C ~ 60°C
Humidity	max. 95%, relative (non-condensing)

