NOVUS

16-channel IP Recorder

NVR-6216-H1/LITE





KEY FEATURES



























- •16 x video and audio channels
- •Recording speed up to 480 fps at 3200 x 1800
- •Supports resolution up to 3200 x 1800
- •Recorded stream size: 64 Mb/s in total from all
- •1 x internal place for HDD mounting
- •2 x monitor outputs (HDMI, VGA)
- •Intelligent image analysis

DIMENSIONS

The recorder is dedicated to work with NOVUS 6000 series IP cameras. Detailed data can be found in the compatibility table available in the ${\tt DOWNLOADABLE}$ FILES tab.

IP Cameras	up to 16 channels at 3200 x 1800 resolution (video + audio)
Maximum Supported Camera Resolution	3200 x 1800
Compression	H.264, H.265, H.265+, H.265 Smart
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA (up to 2 monitors simultaneously)
Dualstreaming Support	yes
Fisheye Support	yes, 6000 IP series cameras • using any web browser, ipGO 6, N Control 6000
AUDIO	
Audio Input/Output	- / 1 x HDMI
RECORDING	
Stream Size	64 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, alarm input, motion detection, intelligent image analysis functions
Prealarm/Postalarm	up to 5 s/up to 600 s

DISPLAY

Display Speed 480 fps (16 x 30 fps)

PLAYBACK

Playback Speed 270 fps (9 x 30 fps) Recorded Data Search by date/time, events, image analysis events, POS, motion in a defined area, tags, license plate number

BACKUP

Backup Methods	USB port (HDD or Flash memory), network	
Backup File Format	AVI, RPAS (player included)	
STORAGE		

Internal Storage	available mount: 1 x HDD 3.5" 10 TB SATA
Total Internal Capacity	10 TB

ALARM	ARM	
Camera Alarm Input/Output	supports IP camera's alarm input/output	
Motion Detection	supports camera's motion detection	





NoVus



255 mm





16-channel IP Recorder NVR-6216-H1/LITE

System Reaction to Alarm Events

buzzer, alarm output activation, recording activation, PTZ, e-mail with atatchment, Full Screen, PUSH message, voice prompt, snapshot

INTELLIGENT IMAGE ANALYSIS

Supported Functions	Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire,
	Zone entrance, Abandoned Object, Object Disappearance, Crowd
	detection, Face Detection, Cross Counting, Fire detection,
	Temperature measurement, Video metadata

NETWORK

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, IEEE 802.1X, PPPoE, SMTP, P2P, POS, HTML5
PC/MAC Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000
Mobile applications	ipGO 6 (iPhone, Android)
Number of Simultaneous Conne	ctionsup to 64 clients, up to 20 main streams or 64 substreams or 16

Number of Simultaneous Connectionsup to 64 clients, up to 20 main streams or 64 substreams or 16 playback streams in total

Bandwidth 64 Mb/s in total to all client workstations

PTZ

PTZ Functions pan/tilt/zoom, preset commands

AUXILIARY INTERFACES

USB Ports 2 x USB 2.0

OPERATING SYSTEM

Operating System	Linux
OSD	languages: Polish, English, others
Control	PC mouse (in-set included), network
System Diagnostic	automatic control of: HDDs, network, camera connection loss
Security	password protection, IP filtering, MAC filtering, ARP guard

INSTALLATION PARAMETERS

255 (W) x 42 (H) x 233 (D)
0.7 kg (without HDD)
12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
18 W (with 1 HDD)
-10°C ~ 50°C

The availability of individual functions (including image analysis) depends on the model of the cameras used, as well as the software version of the recorder and cameras.

Presented display and playback speeds are achieved using dual-streaming. Detailed data on hard drives can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

"INGENIUS PLUS" features support means, that "INGENIUS" is also supported



