

# Monitor

## SMQ-5501



### KEY FEATURES

- LED backlight
- Function preventing from burning-in static images on the LCD panel

### LCD PANEL

Panel Type	TFT, LED backlight
Screen Size (Diagonal)	54.6"
Panel Resolution	3840 x 2160
Brightness	350 cd/m2
Contrast Ratio	1200:1
Viewing Angle (H/V)	178°/178°
Response Time	5 ms
Display Color	1073 mln

### OTHER FUNCTIONS

Built-in Speakers	2 x 5 W
Digital Filter	3D

### INTERFACES

Video Input	1 x CVBS, BNC connector (loop-through), 1 x VGA, 1 x HDMI, 1 x DVI
Audio Input	1 x Mini Jack stereo
External Control	LAN RJ-45, RS-232 9-Pin D-Sub, Infrared remote control
Other Connectivity	USB 2.0

### INSTALLATION PARAMETERS

Dimensions (mm)	1243.2 (W) x 714.0 (H) x 69.6 (D)
Weight	14.8 kg
Case	black, metal
Power Supply	100 ~ 240 VAC
Power Consumption	99 W (max) • 0.5 W (in standby mode) • 0.3 W (in off mode)
Operating Temperature	0°C ~ 40°C
Humidity	max. 85%, relative (non-condensing)
Mounting Standard	VESA 400 x 400 mm