

# Monitor

## LW-2402



### KEY FEATURES

- dedicated to continuous operation (24/7)
- anti-glare panel coating eliminating reflections
- LED backlight

### LCD PANEL

|                        |                   |
|------------------------|-------------------|
| Panel Type             | VA, LED backlight |
| Screen Size (Diagonal) | 23.8"             |
| Panel Resolution       | 1920 x 1080       |
| Brightness             | 250 cd/m2         |
| Contrast Ratio         | 20000000:1        |
| Viewing Angle (H/V)    | 178°/178°         |
| Response Time          | 5 ms              |
| Display Color          | 16.7 mln          |

### OTHER FUNCTIONS

|                   |         |
|-------------------|---------|
| Built-in Speakers | 2 x 1 W |
|-------------------|---------|

### INTERFACES

|             |                      |
|-------------|----------------------|
| Video Input | 1 x VGA, 1 x HDMI    |
| Audio Input | 1 x Mini Jack stereo |

### INSTALLATION PARAMETERS

|                       |  |
|-----------------------|--|
| Dimensions (mm)       | 565.3 (W) x 430.0 (H) x 180.8 (D)                            |
| Weight                | 2.8 kg   |
| Power Supply          | 100 ~ 240 VAC  |
| Power Consumption     | 15.5 W (max) • 0.5 W (in standby mode) • 0.3 W (in off mode) |
| Operating Temperature | 0°C ~ 40°C   |
| Humidity              | 20% - 85%, relative (non-condensing)                         |
| Mounting Standard     | VESA 100 x 100 mm  |