

Monitor

TTN-3201



KEY FEATURES

- dedicated to continuous operation (24/7)
- anti-glare panel coating eliminating reflections
- Function preventing from burning-in static images on the LCD panel

LCD PANEL

Panel Type	IPS
Screen Size (Diagonal)	31.5"
Panel Resolution	1920 x 1080
Brightness	450 cd/m2
Contrast Ratio	1000:1
Viewing Angle (H/V)	178°/178°
Response Time	5 ms
Display Color	16.7 mln

OTHER FUNCTIONS

Built-in Speakers	2 x 10 W
-------------------	----------

INTERFACES

Video Input	1 x CVBS, BNC connector (loop-through), 1 x VGA, 1 x HDMI, 1 x DVI
Audio Input	1 x Mini Jack stereo
External Control	LAN RJ-45, RS-232 9-Pin D-Sub, Infrared remote control
Other Connectivity	USB 2.0

INSTALLATION PARAMETERS

Dimensions (mm)	758.4 (W) x 454.2 (H) x 84.5 (D)
Weight	10.2 kg
Case	black, metal
Power Supply	100 ~ 240 VAC
Power Consumption	50 W (max) • 0.5 W (in standby mode)
Operating Temperature	0°C ~ 40°C
Humidity	20% - 80%, relative (non-condensing)
Mounting Standard	VESA 100 x 100 mm