

Monitor

TTN-4301



KEY FEATURES

- dedicated to continuous operation (24/7)
- anti-glare panel coating eliminating reflections
- Function preventing from burning-in static images on the LCD panel

LCD PANEL

Panel Type	IPS
Screen Size (Diagonal)	43.0"
Panel Resolution	3840 x 2160
Brightness	450 cd/m2
Contrast Ratio	1200:1
Viewing Angle (H/V)	178°/178°
Response Time	5 ms
Display Color	1070 mln

OTHER FUNCTIONS

Built-in Speakers	2 x 12 W
-------------------	----------

INTERFACES

Video Input	1 x CVBS, BNC connector (loop-through), 1 x VGA, 1 x HDMI, 1 x DVI
Audio Input	1 x Mini Jack stereo
External Control	LAN RJ-45, RS-232 9-Pin D-Sub, Infrared remote control
Other Connectivity	USB 2.0

INSTALLATION PARAMETERS

Dimensions (mm)	1002.0 (W) x 591.6 (H) x 84.7 (D)
Weight	19 kg
Case	black, metal
Power Supply	100 ~ 240 VAC
Power Consumption	82 W (max) • 0.5 W (in standby mode)
Operating Temperature	0°C ~ 40°C
Humidity	20% - 80%, relative (non-condensing)
Mounting Standard	VESA 400 x 200 mm