

24-port PoE+ Switch NVS-3324SP-A




KEY FEATURES



KEY FEATURES

- 24 x 100Mbps PoE+
- 2 x Combo (RJ45 + SFP) 1000Mb/s UPLINK
- Operation mode: VLAN, Extend, QoS, PoE Watchdog

DIMENSIONS



GENERAL

Device Type PoE+ Switch

NETWORK

Ports	PoE+ Ports: 24 x 10/100Mbps (the number of ports simultaneously operating with PoE + mode is limited by PoE budget) • Uplink Combo x 2 :SFP (1Gbps) + RJ45 (1Gbps)
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
PoE mode	Endspan (1,2+ / 3,6-)
Switching capacity	8.8 Gb/s
Supported protocols	IEEE 802.3 10BASE-T, IEEE 802.3i 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3z 1000BASE-SX\LX
MAC address list	16K

FUNCTIONS

CCTV	Extend mode switch that increases the data and power transmission distance up to 250m (Using 10 Mb/s bandwidth)
Additional operating modes	VLAN, Extend, QoS, PoE Watchdog

INSTALLATION PARAMETERS

RACK Mount 19"	1U
Case	Metal, navy blue color
Dimensions (mm)	320 (W) x 44 (H) x 207 (L)
Weight	2.2 kg
Input Voltage	100 ~ 240 VAC, 50/60Hz
Power Consumption	370 W
PoE Budget	360 W for ports 1 to 24, up to 30 W for one port
Operating Temperature	0°C ~ 40°C