NoVus

5MPX IP camera with motorzoom lens, Deep Learning-based image analysis and active deterrence

NVIP-5VE-4512M/FWLAD





KEY FEATURES































- •Resolution: 5 MPX
- •Lens: motorized, auto-focus function, f=2.8 \sim 12 mm/F1.2
- support for Chrome, Firefox, Opera, Safari browsers
- \bullet D/N function IR cut filter
- •Video content analysis based on Deep Learning
- •Licence plate recognition (LPR)
- microSD card support
- WDR with double scan sensor
 two-way audio
- •Min. Illumination: 0.003 lx (0 lx, IR on)
- •IR LED, range up to 30 m •white LED illuminator, range up to 20 m
- "Two way power" when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

COMPLIANCE



DIMENSIONS

The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

IMAGE

IIIAGE	
Image Sensor	5 MPX CMOS sensor 1/2.7" SmartSens
Number of Effective Pixels	2880 (H) x 1620 (V)
Min. Illumination	0.003 lx/F1.2 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

LENS

Lens Type	motorized, $f=2.8 \sim 12$ mm/F1.2
Auto-focus	zoom trigger, manual trigger

DORI

DORI (Detection, Observation,	for f = 2.8mm - D: 56m, O: 22.4m, R: 11.2m, I: 5.6m • for f = 12mm -
Recognition, Identification)	D: 240m, O: 96m, R: 48m, I: 24m

DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Schedule	yes

NETWORK

Stream Resolution	2880 x 1620, 2560 x 1440 (QHD), 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3 (main stream, sub stream, third stream)
Video/Audio Compression	H.264, H.264+, H.265, H.265+/G.711
Number of Simultaneous Conne	ectionsmax. 10
Bitrate	for H.264 : 8 kbps - 8192 kbps • for H.265 : 8 kbps - 8192 kbps





NoVus



128 mm

135 mm (Ø)



5MPX IP camera with motorzoom lens, Deep Learningbased image analysis and active deterrence NVIP-5VE-4512M/FWLAD

Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, SMTP, P2P, HTML5, RTMP
ONVIF Protocol Support	Profile G/S/T/M
Camera Configuration	from Edge, Firefox, Chrome, Opera, Safari browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC
Mobile applications	ipGO 4 (iPhone, Android)
VIDEO ANALYTICS	
Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, zone exit, multi loiter, face detection, pedestrian detection, cross counting, heat map, queue length detection, objects distinguishing, vehicle detection, intrusion detection, smart motion detection with objects distinguishing
OTHER FUNCTIONS	
Security	video encryption, IEEE 802.1X support, HTTPS support, MAC/IP address filtering, force change of default password
Privacy Zones	4 video mask type: single color
Motion Detection	yes
Region of interest (ROI)	8
Audio Detection	yes
Image Processing	180° image rotation, corridor mode, vertical flip, horizontal flip
Prealarm/Postalarm	up to 5 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, HTTP notification, active deterrent functions
Determent	white LEDs, steady/flashing light, red and blue LEDs, flashing light, • audio signaling device (siren), built-in speaker (predefined or custom voice messages)
Restoring default settings	via web browser, using reset button
LICENCE PLATE RECOGNITION	I (I PR)
Autonomous operation mode	yes - recognition function implemented in the camera
Capacity of License Plate Database	up to 10000 license plates, on all lists.
Types of recognized number plates	all countries of the European Union
Data recorded in the camera base	recognition date/time, number of recognised licence plate, image of recognised licence plate, presence on the "white list" or "black list"
Reactions for the licence plate recognition	e-mail with attachment, saving file on FTP server
IR LED	
LED Number	2
Range	30 m
Smart IR	yes (hardware support)
WHITE LIGHT ILLUMINATOR	
LED Number	2, warm white color
Range	20 m
INTERFACES	
Audio Input/Output	built-in microphone/speaker





5MPX IP camera with motorzoom lens, Deep Learningbased image analysis and active deterrence NVIP-5VE-4512M/FWLAD

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
INSTALLATION PARAMETE	RS
Dimensions (mm)	135 (Ф) x 128 (H)
Weight	0.9 kg
Degree of Protection	IP 67 (details in the user's manual)
Enclosure	vandalproof, aluminium, white • enclosure type: 4VE-B
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Surge protection	TVS 4000 V
Power Consumption	2 W • 5 W (IR illuminator on) • 5 W (white light illuminator on) • 6 W (active deterrence functions enabled)
Operating Temperature	-35°C ~ 60°C
Humidity	max. 90%, relative (non-condensing)

A memory card is required for the license plate recognition functions to work. AAT SYSTEMY BEZPIECZEŃSTWA sp. z o.o. hereby declares, that this NOVUS product does not contain any components or technologies manufactured by the entities mentioned in the Section 889 of the National Defense Authorization Act (NDAA) for Fiscal Year 2019

