NoVus

8 MPX Bullet IP Camera

NVIP-8H-6511/F-II





KEY FEATURES





















- •Resolution: 8 MPX (4K Ultra HD)
- •Lens: fixed focal, f=2.8 mm/F1.6
- Human/Vehicle Object Classification
- •D/N function IR cut filter
- •Video content analysis based on Deep Learning
- microSD card support
- $\bullet \mathsf{WDR} \mathsf{\ with\ double\ scan\ sensor}$
- •Min. Illumination: 0.02 lx (0 lx, IR on)
- •IR LED, range up to 50 m

DIMENSIONS





81 mm





The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the $\ensuremath{\mathsf{DOWNLOADABLE}}$ FILES tab.

IMAGE

| 8 MPX CMOS sensor 1/2.8" SONY STARVIS |
|---|
| 3864 (H) x 2192 (V) |
| 0.02 lx/F1.6 - color mode • 0 lx (IR on) - B/W mode |
| auto/manual: 1/3 s ~ 1/100000 s |
| up to 1/3 s |
| yes (double scan sensor), 120dB |
| yes |
| 3D |
| yes |
| yes |
| yes |
| yes |
| |

LENS

| Lens Type | fixed focal, f=2.8 mm/F1. |
|-----------|------------------------------|
| Lens Type | 11Xeu 10cai, 1-2.0 11111/1 1 |

DORI

| DORI (Detection, Observation, | for f = 2.8mm - D: 83m, O: 33m, R: 17m, I: 8m |
|-------------------------------|---|
| Recognition, Identification) | |

DAY/NIGHT

| Mode | day/night switching: mechanical IR cut filter |
|----------------------------|---|
| Switching Mode | auto, manual, time |
| Switching Level Adjustment | yes |
| Switching Delay | 2 ~ 120 s |
| Switching Schedule | yes |
| Visible Light Sensor | yes |

NETWORK

| TIL I TOTAL | |
|---------------------|---|
| Stream Resolution | 3840×2160 (4K Ultra HD), 3072×2048 , 2560×1440 (QHD), 2592×1520 , 2592×1944 , 2304×1296 , 1920×1080 (Full HD), 1280×720 (HD), 640×480 (VGA), 320×240 (QVGA), 480×240 |
| Frame Rate | 30 fps for each resolution • 60 fps for the following resolutions: 1920 x 1080 (Full HD) |
| Multistreaming Mode | number of streams: 3 |
| | |



NoVus

8 MPX Bullet IP Camera NVIP-8H-6511/F-II

| Video/Audio Compression | H.264, H.264+, H.265, H.265+, MJPEG/G.711 |
|-----------------------------------|--|
| Number of Simultaneous Connection | nsmax. 10 |
| Bitrate | for H.264 : 128 kbps - 12288 kbps • for H.265 : 64 kbps - 8192 kbps |
| Network Protocols Support | HTTP, TCP/IP, IPv4, IPv4/v6, UDP, HTTPS, FTP, DHCP, DDNS, NTP, RTSP, UPnP, SNMP, IEEE 802.1X, PPPoE, SMTP, RTCP, ICMP, SSL/TLS, HTML5 |
| Camera Configuration | from Edge, Firefox, Chrome, Opera browser • languages: Polish, English, and others |
| Compatible Software | NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000 |
| Mobile applications | ipGO 6 (iPhone, Android) |
| VIDEO ANALYTICS | |
| Functions | tamper, abandoned object, object disappearance, line cross, zone entrance, zone exit, loiter, face detection, detection of people not wearing masks, cross counting, heat map, scene change, video blurred, video color cast, objects distinguishing, people counting, vehicle counting, intrusion detection, target counting by area, video metadata, illegal parking detection |
| OTHER FUNCTIONS | |
| Security | video encryption, configuration encryption, IEEE 802.1X support, HTTPS support, Basic authorization for HTTP/RTSP, Digest authorization for HTTP/RTSP, MAC/IP address filtering, force change of default password |
| Privacy Zones | 4 video mask type: single color or 4 video mask type: mosaic |
| Motion Detection | yes |
| Region of interest (ROI) | 8 |
| Audio Detection | yes |
| Image Processing | 90° image rotation, 180° image rotation, sharpening, mirror effect, corridor mode, vertical flip, horizontal flip, lens distortion correction |
| Prealarm/Postalarm | up to 6 s/up to 120 s |
| System Reaction to Alarm Events | e-mail, e-mail with attachment, saving file on FTP server, saving file on SD card |
| Restoring default settings | via web browser, using reset button, via NMS IPTool software |
| IR LED | |
| LED Number | 2 |
| Range | 50 m |
| Smart IR | yes (software support) |
| INTERFACES | |
| Audio Input/Output | 1 x Jack (3.5 mm)/- |
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s |
| Memory Card Slot | microSD - capacity up to 256GB |
| INSTALLATION PARAMETERS | |
| Dimensions (mm) | with bracket: 81 (W) x 81 (H) x 220 (L) |
| Weight | 0.7 kg |
| Degree of Protection | IP 67 (details in the user's manual) |
| Power Supply | 12 VDC, PoE (IEEE 802.3af, Class 3) |
| Surge protection | TVS 4000 V |
| | |







8 MPX Bullet IP Camera NVIP-8H-6511/F-II

| Power Consumption | 7 W • 11 W (IR illuminator on) |
|-----------------------|-------------------------------------|
| Operating Temperature | -30°C ~ 60°C |
| Humidity | max. 95%, relative (non-condensing) |

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).



