

## 8 MPX IP camera with Deep Learning-based image analysis

**NVIP-8H-4231/WL**

4000 VSS IP



### KEY FEATURES



- Resolution: 8 MPX (4K Ultra HD)
- Lens: fixed focal, f=2.8 mm/F1.6
- built-in microphone
- D/N function - IR cut filter
- Video content analysis based on Deep Learning
- microSD card support
- Min. Illumination: 0.009 lx (0 lx, IR on)
- IR LED, range up to 25 m
- white LED illuminator, range up to 20 m
- "Two way power" - when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

### DIMENSIONS



The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the **DOWNLOADABLE FILES** tab.

### IMAGE

Image Sensor	8 MPX CMOS sensor 1/2.7" SmartSens
Number of Effective Pixels	3840 (H) x 2160 (V)
Min. Illumination	0.009 lx/F1.6 - color mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes

### LENS

Lens Type	fixed focal, f=2.8 mm/F1.6
-----------	----------------------------

### DORI

DORI (Detection, Observation, Recognition, Identification)	for f = 2.8mm - D: 74m, O: 30m, R: 15m, I: 7m
--	---

### DAY/NIGHT

Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Schedule	yes

### NETWORK

Stream Resolution	3840 x 2160 (4K Ultra HD), 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA)
Frame Rate	15 fps for each resolution
Multistreaming Mode	number of streams: 2 (main stream, sub stream)
Video/Audio Compression	H.264, H.265/G.711
Number of Simultaneous Connections	max. 4
Bitrate	for H.264 : 128 kbps - 6144 kbps • for H.265 : 128 kbps - 6144 kbps
Network Protocols Support	HTTP, TCP/IP, IPv4, HTTPS, DHCP, DNS, DDNS, NTP, RTSP, RTP, SMTP, P2P
Camera Configuration	from Edge browser • languages: Polish, English, and others

# 8 MPX IP camera with Deep Learning-based image analysis NVIP-8H-4231/WL

Compatible Software	NOVUS MANAGEMENT SYSTEM VSS
---------------------	-----------------------------

Mobile applications	ipGO 4 (iPhone, Android)
---------------------	--------------------------

## VIDEO ANALYTICS

Functions	line cross, zone entrance, zone exit, zone violation, intrusion detection, smart motion detection with objects distinguishing
-----------	---

## OTHER FUNCTIONS

Security	HTTPS support, force change of default password
----------	---

Privacy Zones	4 video mask type: single color
---------------	---------------------------------

Motion Detection	yes
------------------	-----

Audio Detection	decline detection, rise detection
-----------------	-----------------------------------

Image Processing	180° image rotation, vertical flip, horizontal flip
------------------	---

Prealarm/Postalarm	up to 5 s/up to 30 s
--------------------	----------------------

System Reaction to Alarm Events	e-mail with attachment, saving file on SD card, active deterrent functions
---------------------------------	--

Determent	white LEDs, steady/flashing light,
-----------	------------------------------------

Restoring default settings	via web browser, using reset button
----------------------------	-------------------------------------

## IR LED

LED Number	1
------------	---

Range	25 m
-------	------

Smart IR	yes (hardware support)
----------	------------------------

## WHITE LIGHT ILLUMINATOR

LED Number	2, warm white color
------------	---------------------

Range	20 m
-------	------

Smart Light	yes (hardware support)
-------------	------------------------

## INTERFACES

Audio Input/Output	built-in microphone
--------------------	---------------------

Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
-------------------	---

Memory Card Slot	microSD - capacity up to 256GB
------------------	--------------------------------

## INSTALLATION PARAMETERS

Dimensions (mm)	with bracket: 71 (Φ) x 147 (L)
-----------------	--------------------------------

Weight	0.38 kg
--------	---------

Degree of Protection	IP 67 (details in the user's manual)
----------------------	--------------------------------------

Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included • enclosure type: 4H-B
-----------	---

Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
--------------	-------------------------------------

Power Consumption	2 W • 3 W (IR illuminator on) • 4 W (white light illuminator on)
-------------------	--

Operating Temperature	-35°C ~ 60°C
-----------------------	--------------

Humidity	max. 90%, relative (non-condensing)
----------	-------------------------------------

AAT SYSTEMY BEZPIECZEŃSTWA sp. z o.o. hereby declares, that this NOVUS product does not contain any components or technologies manufactured by the entities mentioned in the Section 889 of the National Defense Authorization Act (NDAA) for Fiscal Year 2019