NoVus

Digital Video Recorder

NDR-BA5208





KEY FEATURES




















- •IP video channels: 1
- •Internal HDDs mount: up to 1
- •Monitor outputs: 4 (3 x main, 1 x spot)
- •Advanced network software
- •Supports 700 TVL cameras (960H)
- •IP cameras support (hybrid mode)


COMPLIANCE







DIMENSIONS



VIDEO

Video Input	8 x BNC
IP Cameras	Channels number: 1 at 1920 x 1080 resolution *
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI, 1 x VGA, 1 x BNC • spot (full screen, sequence): 1 x BNC

AUDIO

Audio Input/Output 4 x RCA/1 x RCA

RECORDING		
Compression	H.264	
Recording Speed	200 fps (720 x 576) • 200 fps (720 x 288) • 200 fps (360 x 288) • 100 fps (960 x 576)	
Recording Speed (IP Cameras)	25 fps (1 x 25 fps for 1280 x 720) • 12 fps (1 x 12 fps for 1920 x 1080)	
IP Stream Size	6 Mb/s in total from all cameras	
Recording Mode	time-lapse, triggered by: REC/PANIC button, alarm input, motion detection	
Schedule	individual settings for: each camera, each day of the week, configuration with an accuracy of: 60 min, possibility of combining individual recording modes	
Prealarm/Postalarm	up to 30 s/up to 5 min	

PLAYBACK

LAIDACK	
Playback Speed	200 fps (25 fps per channel)
Playback Speed (analog channels)	200 fps (25 fps per channel)
Playback Speed (IP channels)	25 fps (25 fps per channel)
Recorded Data Search	by date/time, events

BACKUP

Backup Methods

Backup File Format	AVI, DAT
STORAGE	
Internal storage	available mount: 1 x HDD 3.5" SATA (without DVD-RW) **

4 TB

USB port (HDD or Flash memory), network

ALARM

Total Capacity

Alarm Input/Output	8/1 relay type
Motion Detection	22 x 15 grid, individual settings of sensitivity
System Reaction to Alarm Events	buzzer, e-mail, alarm output activation, screen message, recording activation







Digital Video Recorder NDR-BA5208

Power Consumption

Operating Temperature

NETWORK	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
PC/MAC Software	B-Viewer, CMS, NMS, Internet Explorer/-
Mobile applications	SuperLivePro (iPhone, Android), SuperLiveHD (iPhone, Android)
Max. Number of Connections with DVR	7 (live monitoring: 5, playback: 1, configuration: 1)
PTZ	
PTZ Ports	1 x RS-485
PTZ Protocols	N-Control, Pelco-D, Pelco-P, others
PTZ Functions	pan/tilt/zoom, preset commands, patterns, tours, auto-scans
AUXILIARY INTERFACES	
USB Ports	2 x USB 2.0
OPERATING SYSTEM	
Operating System	Linux
Operation Mode	quadruplex
OSD	languages: Polish, English, Russian, others
Control	front panel, PC mouse and IR remote controller (in-set included), network, NV-KBD70, NV-KBD50, NV-KBD30 keyboards
System Diagnostic	automatic control of: HDDs
INSTALLATION PARAMETERS	
Dimensions (mm)	300 (W) x 65 (H) x 280 (D)
Weight	2 kg (without HDDs)
Power Supply	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)

25 W (with 1 HDD) 0°C ~ 50°C





^{*} Feature available for DVRs with 3.4.3.U-3520D-11 2015-04-04 (Launch date) or later firmware version. DVR is compatible with Novus IP 3000 cameras.

^{**} List of compatible HDD models and maximum of their capacities is available in section DOWNLOADABLE FILES.