
8-Port Ethernet PoE+ Switch

NVS-3408SP



KEY FEATURES

NDAA

KEY FEATURES

- 8 x 10/100Mbps PoE+
- 2 x 10/100/1000Mb/s UPLINK
- Operation mode: VLAN, Extend, PoE Watchdog

DIMENSIONS







GENERAL

Device Type	PoE+ Switch

NETWORK

Ports	PoE+ Ports: 8 x 10/100Mbps (the number of ports simultaneously operating with PoE mode is limited by PoE budget) • Uplink ports: 2 x 10/100/1000Mbps
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
PoE mode	Endspan (1,2+ / 3,6-)
Switching capacity	5.6 Gb/s
Supported protocols	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3x
MAC address list	2K

FUNCTIONS

CCTV	Extend mode switch that increases the data and power transmission distance up to 250m (Using 10 Mb/s bandwidth)
Additional operating modes	VLAN, Extend, PoE Watchdog
Surge protection	Port Surge: Common mode 4kV, differential mode 2kV (Class B) • Electrostatic ESDP: Air 8kV, Contact 6kV (Class C)

INSTALLATION PARAMETERS

Case	Metal, black color
Dimensions (mm)	200 (W) x 44 (H) x 118 (L)
Weight	1 kg
Input Voltage	100 ~ 240 VAC, 50/60Hz
Power Consumption	100 W
PoE Budget	95 W for ports 1 to 8, no more than 60 W for the first port, 30 W for the remaining ports
Operating Temperature	0°C ~ 40°C